
# INFORMATION FOR FIRST AND SECOND RESPONDERS

# **EMERGENCY RESPONSE GUIDE FOR VEHICLE**



Alexander Dennis Enviro200EV

Battery-Electric Vehicle

Electric Motor Propulsion











# Enviro200ev

Document Ref: 4020-2 Enviro200EV TfL ERG Doc Standard: ISO 17840-3 Date: Sep 2025


# ContentsExample Rescue SheetPage 41. Propulsion IdentificationPage 5 - 72. Immobilisation / Stabilisation / LiftingPage 8 - 93. Disable Direct Hazards / Safety RegulationsPage 10 - 124. Access to the OccupantsPage 13 - 145. Stored EnergyPage 15 - 186. In Case of FirePage 19 - 227. In Case of SubmersionPage 238. Towing / Transportation / StoragePage 24 - 279. Important Additional InformationPage 2810. Explanation of Pictograms UsedPage 29Safety Data SheetsAppendix

Download this, and other safety documents, from <a href="https://www.ad24.direct/emergency-response">https://www.ad24.direct/emergency-response</a>



### **Rescue Sheet**

This provides necessary and useful information about a vehicle involved in an accident/incident to support the rescue team in rescuing the vehicle occupants as quickly and safely as possible. It should be used by first responders to assist in making a safe rescue plan. The full version is available as a separate document.



### 1. Propulsion Identification



**CAUTION:** Lack of noise does not mean vehicle is off: Silent movement or instant restart capability exists until vehicle is fully shut down

### **Vehicle Description**

The Enviro200Ev is a fully electric powered, two axle, two door, single deck midibus.

The vehicle is fitted with 12 re-chargeable lithium-iron-phosphate (LFP) battery packs.

The vehicle is driven by a water-cooled, permanent magnet, Voith Electrical Drive System (VEDS) HD Electric Motor with a high-efficiency inverter.

If there is a model badge on the vehicle it may look like one of the following pictures.

Not all models will display all the badges

# Enviro200ev





### **Vehicle Identification**

There is an identification plate located inside the front door on the right hand bulkhead. This plate gives details of:

- Manufacturer
- Model
- Permitted Weights
- VIN number



### **HV Battery Pack Details**

12 x LFP lithium-ion battery packs Chemical class: ADR Class 9A – miscellaneous dangerous goods Nominal operating voltage: 750VDC











### **Critical Component Locations (Vehicle Exterior).**






### 1. Propulsion Identification

### Chassis HV and equipment Layout.

NOTE: HV shocks are a potential risk where any component damage is suspected.



### 2. Immobilisation / Stabilisation / Lifting

Suspension height controls are located on the right hand side of the driver's switch console

### Suspension Controls.



Access to the suspension control is from within the driver's cab. **NOTE:** These controls only operate when the vehicle is fully powered on.



### Suspension raise.



### For front kneeling:

Press and hold the lower switch until lowering reaches required level. Press the upper switch once and the vehicle will return to normal ride height.

### **Preventing Vehicle Motion.**

Ensure the parking brake is applied before leaving the vehicle. Where this is not possible, the wheels should be chocked to prevent any unwanted movement.







### **⚠ WARNING:**

In the event of electrical failure, the Electronic Parking Brake will not respond and wheel chocks MUST be used to prevent runaway.

### 2. Immobilisation / Stabilisation / Lifting

### Lifting points.


Lift the bus as indicated in the below illustration - behind the front axle and just behind the rear axle. Attempting a lift elsewhere carries a high risk of damage.



Lifting points are as marked.

Do not lift forward of the front axle, in the centre of the body or forward of the rear axle as the structure in these locations is unsuitable for supporting the weight of the vehicle.

The lift will be unstable and may cause damage or injury. to personnel



### Stabilisation points / chassis support points

Lifting equipment should be applied to the jacking points on the chassis frame.




Front RHS Jacking Point


Rear RHS Jacking Point.



### **Chassis Support Locations**

Yellow circles indicate jacking locations when lifting the vehicle





### 3. Disable Direct Hazards / Safety Regulations

CAUTION: Always engage the parking brake before leaving the cab OR chock the wheels to prevent movement

### Vehicle Safe Shutdown Procedure.






# 2 Apply the Electronic Parking Brake.

Access to the parking brake control is from within the driver's cab.

To apply the parking brake, pull the lever up. When the park brake is applied, the park symbol within the lever will illuminate **RED** and the park warning light will show in the telltale display on the instrument binnacle.

If the vehicle has no electrical power the parking brake control will not function, suitable precautions should be taken in order to prevent unintended movement. Wheel chocks should be applied to at least one wheel.






# 3 Turn off Ignition:

To shut down the bus, press the lower part of the Start/Stop switch. Switch will flash during power-down, wait 10 seconds before proceeding.



# 4 Turn off Master Switch:

Press and release the bottom of the switch to turn off the master switch. Switch will flash during power-off.








### To confirm that vehicle is powered off:

- · No illumination on instrument cluster
- · No lights on master or Ignition switches



### 3. Disable Direct Hazards / Safety Regulations

### Emergency Vehicle Shutdown (ALL HV & 24V Systems).



### **Emergency Stop: Driver's Cab.**

Switch is in the side console towards the back of the driver's seat.

Lift cover and push toggle to activate the emergency stop.











### **Emergency Stop: Offside Rear.**

Switch is on the right hand side rear of the bus, behind the coolant tank access door.

Open the door and twist the switch to activate the emergency stop.

Hold for 5 seconds or longer.

### **Emergency Stop: Rear Drive Bay.**

If possible, switch off vehicle before operating.

Lift cover: CAUTION: gas struts on lid.

Push stop button until it latches to activate the emergency stop. This button can be padlocked to prevent accidental release.



### **Emergency Stop: Resetting.**

Following activation of any Emergency Stop control, there is a 2-minute wait period after the switch is released.

During this time, no attempt should be made to be turn the bus on again. After the 2 minutes has elapsed, the start-up sequence can be initiated.




If a start up is attempted before the 2 minutes has elapsed, the vehicle will enter an error state and will require a reset action to be carried out.

This is achieved by turning off the ignition and master switches, then disconnecting the LV batteries (using the disconnect switch, if fitted) for at least 2 minutes.

After this time, the bus can be reconnected and the start-up sequence followed as usual.

### 3. Disable Direct Hazards / Safety Regulations

### 24V Disconnection.






Battery access is via an access door at the front, below the driver's cab.

The 24v Battery Disconnect switch is found at the rear of the battery compartment Rotate the switch to the OFF position.

The switch can be secured with a padlock if necessary



### **Alternate Method**

Lift and secure the access door, release the antiluce fasteners, then slide the tray out to access the battery connectors and remove the negative terminal connection. Secure cable to prevent accidental re-connection.



### **High Voltage Disconnection.**





### **WARNING:**

Do not disturb the MSD plugs if the vehicle is on charge.

Stop and remove charge supply before touching.

Failure to do so may result in danger to life or damage to equipment.

To access the Manual Service Disconnect plugs on the High Voltage Junction Box, open the rear drive bay door.


### On both MSD plugs:

Release the locking tabs before lifting the lever to 90°.

Pull the plugs out of the High Voltage Junction Box.







The removed plugs should be stored safely until they are needed. AD recommends placing them in a padded bag and putting them on the binnacle to prevent any accidental reconnection. Close the access door to prevent rain or moisture ingress.

A warning should be placed on the steering wheel to indicate the vehicle is not to be powered up.



### 4. Access to the Occupants



### **Emergency Door Operation.**



To open the door from outside:

Push the emergency button located near the rear edge of the doors.


To open the door from inside:

Push the emergency button located above the doors.

Lift the flap and push the button.







Internal Emergency Exit Button

### **Door Operation Failure.**

If the doors do not operate they can be pushed open manually. It may be necessary to exhaust any remaining air in the auxiliary system.



Front/entrance doors:

Push the outer edge inwards, then pivot the door into the bus.





Rear Emergency Exit:

From outside: Grip the handle and pull the door open

Then slide the door to the side

From inside: Push the door open

Then slide the door to the side






### 4. Access to the Occupants

### Driver's Cab Door.

To open the driver's door, where possible, reach in and lift the handle to release the door.

Where this is impractical or not available, it may be necessary to insert a T-key into the hole on the outside of the cab door and twist to release the door lock





### Door Controls in Driver's Cab.

The door control switches are on the right hand side of the instrument panel.

The buttons are not operative if:

- · The vehicle is switched off.
- The vehicle is moving.
- · The park brake is OFF.
- The system air pressure is too low.

Press the lower switch to open the doors.

Press the upper switch to close the doors.

The switch will flash during opening and closing and remain illuminated while the door is open.







Instrument Panel Switch Location

### Steering Column Adjustment.

The vehicle is fitted with an air adjustable steering column. The foot operated column adjustment switch is mounted in the floor plate directly behind the column.

To adjust the column position, the park brake must be applied. Grasp the steering wheel and depress the foot button, move the steering wheel as required for either driving or access.

If there is no air in the system, the adjustment mechanism will not release.





### Break Glass Escape windows.



Window break glass buttons are located around the saloon.

The saloon has buttons in 3 locations.

Twist and remove the yellow seal and strike the red button to cause the window to shatter (safety glass) to assist in an emergency exit from inside the vehicle.

The breakable windows are identified from outside the vehicle by the visible break glass sticker in the top of each breakable window.

Rescue personnel may break these windows when required to gain access to the interior of the vehicle.





### HV Battery Detail (Rechargeable Electrical Energy Storage System).

The vehicle is fitted with 12 re-chargeable battery packs with a combined storage capacity of 400KWh. The nominal voltage in the HV system is up to 750VDC.

All High Voltage Battery Packs are lithium-iron-phosphate (LFP) type batteries.


The battery assembly cover should never be breached or removed under any circumstances, including fire. Doing so might result in severe electrical burns, shocks, or electrocution.

### **Battery General Information:**

- Under normal conditions of use, the battery does not present any risk of exposure to its content
- Exposure to high voltage (voltage higher than 60V) may be a risk if the battery casing or HV cables are breached
  or damaged during a collision or subsequent rescue & recovery.
- Exposure to Material / Electrolyte mixture may be a risk if the battery casing is breached
- Always contact medical assistance in the event of exposure to Material / Electrolyte mixture or High Voltage

All the battery packs are liquid cooled. The BTMS (Battery Thermal Management System), traction cooling and the cabin heater & cooling unit use an ethylene-glycol based coolant. This is supplied by Valvoline, under the name "OEM Advantage 48". Full SDS details are in the appendix. After the bus has been running, the coolant will be hot and under pressure. Do not open any caps or breach any hoses, as this poses a risk of scalding liquid or steam being released.

For full details of battery packs fitted, see the SDS in the appendix.



### Thermal Runaway.

There may be risk of re-ignition for up to 48 hours after a fire has occurred.

The vehicle should be guarantined and monitored for at least this time to ensure there is no further risk of fire.

C02, metal fire-ex powder or dry powder extinguisher are recommended by the battery manufacturer. Do not use water to extinguish a battery fire. Check local regulations and alert the local fire service if necessary.

### **HV Battery information:**



### **Summary of Danger**

Warning, do not open or remove, do not expose to flame or open fire. Do not mix batteries with different models, different chemical properties or different types. There is a danger of explosions and burns under the conditions of fire. Do not short-circuit, squeeze, burn or disassemble the battery.

### Classification of the substance or mixture [REGULATION (EC) No 1272/2008]











Flam. Liq. 3: H226 Flammable liquid and vapour.

Skin Corr. 1: H314 Causes severe skin burns and eye damage.

Eye Dam. 1: H318 Causes serious eye damage.

Acute Tox. 4: H302 Harmful if swallowed.

STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

Skin Sens. 1: H317 May cause an allergic skin reaction.

In case of electrolyte leakage from the battery:

Irritation: Irritating to eyes and skin

### **General First Aid Actions**

Apply existing general rules concerning first aid.

Especially, observe the following guidelines:

- Move the injured to a safe place (at least 50 meters from the dangerous area) in the fresh air.
- Perform cardiopulmonary resuscitation (CPR) if the victim is not breathing.
- · Call emergency medical service

### **Electrolyte Exposure Actions:**

- · Consult a doctor immediately.
- Where safe to do so, move the victim into fresh air and keep them calm.
- Remove and isolate contaminated clothing and shoes (of the injured and your own).
- In case of skin contact with electrolyte, immediately flush skin with lukewarm water (with dishwashing soap or soap if available) until medical help arrives; flush eyes with running water until medical help arrives. Consult a doctor if skin irritation persists.
- In case of eye contact with electrolyte rinse continuously with water for at least 10 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Shield unaffected eye. If eye irritation persists get medical advice/attention.
- In case of electrolyte swallowing do NOT induce vomiting. Swallowing may cause gastrointestinal tract burns, nausea, and vomiting.
- After inhalation of vapour or swallowing of electrolyte seek medical help immediately.
- Inform medical personnel of substances and materials involved to ensure appropriate precautions are taken.

### **Electric Shock.**

Personnel who have been exposed to an electric shock should be checked for internal injuries even if they have no visible or obvious symptoms.

### **Environmental Precautions.**

Do not discharge leakages into the drains/surface waters/groundwater, where possible and safe, prevent any fluid escape from entering surrounding watercourses. Absorb the substance with an absorbing agent such as earth, sand or other non-combustible, non-conductive material and dispose of it in a glass container or plastic bag. Dispose of absorbed material in accordance with local regulations.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations

This is a summary, for a full list of safety information, precautions and actions, please refer to the SDS in the appendix

### Compressed Air.




The vehicle uses compressed air for braking, suspension and assorted accessory tasks.

Air is supplied by a High-Voltage air compressor, through a drier and is stored in steel reservoirs distributed around the vehicle.

The air looms are made from PVC which is not fire-resistant and will deform and fail in the event of a fire, possibly resulting in the loss of air pressure.

The Air system runs at a maximum pressure of 10Bar / 130PSIG.

The electric compressor is connected to the HV system and will run on demand all the time the bus is turned on




### Power Steering.

The vehicle is equipped with an electro-hydraulic power steering system. There is a HV pump below the driver's foot plate and a hydraulic reservoir mounted at the front of the vehicle.

In the event of a front impact, the hydraulic fluid may escape if the system is ruptured.








### **Air-conditioning Refrigerant Systems**

BTMS - Battery Thermal Management System plus Traction and Drive Systems Cooling is carried out on the roof of the vehicle in a self-contained pod.



Below the windscreen, is the front demister, with HV connections



There is a compressed refrigerant present within the BTMS and the heating & cooling system.





R407C Refrigerant

H280 - Contains gas under pressure; may explode if heated

Caution: Contact with liquid or refrigerated gas can cause cold burns and frostbite

Please see the SDS in the appendix for full material details on the gas and fluids within these units.

The BTMS, traction cooling and the cabin heater & cooling unit use an ethylene-glycol based coolant. This is supplied by Valvoline, under the name "OEM Advantage 48". Full SDS details are in the appendix.





ETHYLENE GLYCOL

H302 - Harmful if swallowed.

H373 - May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

### 6. In Case of Fire

### Do not submerge to extinguish fire













### DO NOT SPRAY WATER DIRECTLY INTO THE DRIVE BAY.

### **Battery Product identification:**

NMC lithium-ion battery pack

Chemical Class: ADR Class 9 - miscellaneous dangerous goods.

DO NOT USE WATER ON Li-lon BATTERY FIRES:

C02, metal fire-ex powder or dry powder fire extinguishers are acceptable.

WARNING: Do not submerge vehicle to extinguish fire.

**Battery Re-Ignition:** Where a battery fire is experienced or suspected, monitor for at least 48 hours with thermal fire detection equipment, quarantine vehicle where necessary.

### **Drive Bay Fire Warning Light.**

This dashboard light illuminates when one or more rear drive bay fire sensors or system is triggered.



### Hand-held Fire Extinguisher.

There is a hand-operated dry powder fire extinguisher mounted behind the driver in the cab.

This can be used to assist safe exit of passengers from the bus in the event of an internal fire.



### 6. In Case of Fire

### **Battery Pack Access From Outside The Bus.**

When monitoring the vehicle with thermal imaging equipment, these are the areas most likely to be at risk from any HV battery issues



The hashed areas highlight where a thermal imaging monitor may be able to detect an overheating battery.

The floor of the bus has battery packs within the structure.

The rear drive bay has batteries within the frame of the bus.

There are batteries mounted on the roof of the bus in a self-contained pod.





### Rear left-hand side battery locations:

Behind removable access panel



Behind rear side access door



### 6. In Case of Fire

### Fire where batteries are NOT damaged.

Recommendations for extinguishing an electric vehicle fire:

- · Secure the surroundings (prevent access to the fire by outsiders).
- Keep a suitable distance from the fire, pay attention to the wind direction and do not approach "upwind".
- Extinguish the vehicle with water or foam.

Recommendations for extinguishing traction batteries with non-damaged casings:

- · Extinguish with plenty of water (fire takes a long time to extinguish).
- Extinguish from a distance of at least 1 metre from the battery.
- · Do not open or break the battery casing.
- · Check the fire with a thermal imaging camera.

### WARNING.

If using water to extinguish/suppress an HV battery, use a large volume of water. Using only a small amount could allow dangerous toxic gases to be released. If a Lithium Ion HV battery is involved in a fire, there is a possibility that it could reignite after extinguishing. If available, use thermal imaging to monitor the battery. Do not store a vehicle containing a damaged or burned Li-Ion HV battery in or within 50 feet of a structure or other vehicle until the battery can be discharged. Re-ignition of fire in an HV battery pack is typically accompanied by "whooshing" or "popping" sounds, followed by off-gassing of white smoke and/or electrical arcs/sparks that reignited with visible flames/fire. Re-ignition can occur again.

### NOTE.

Because HV batteries are in protective cases, it is very difficult to get any extinguishing agent directly onto the burning cells. The application of large volumes of water may cool the HV battery case sufficiently to prevent the propagation of fire to adjacent cells. Continuous application of water on a localized area of the battery for a prolonged period before moving to another section of the battery provides for quicker extinguishing. Continue to apply water even after the visible flame is no longer present to properly cool the HV battery pack and prevent/reduce the risk of re-ignition. Anticipate longer fire suppression times once the HV battery is involved due to the difficulty in accessing the burning material inside the battery case.

### Event of battery fire where battery case is, or may be, damaged.

### **Extinguishing media**

Follow local fire protection regulations. C02, metal fire-ex powder or dry powder extinguisher are recommended by the battery manufacturer. When the battery is on fire then water is allowed only for cooling the casing of the battery. When the battery is open and cells are visible, water is FORBIDDEN. Non-water extinguishing media only to be used directly on the cells.

### Special hazards arising from the substance or mixture

Hazardous combustion products: carbon monoxide, carbon dioxide, lithium oxide fumes.

Fire as the result of collision/ road accident/ severe impact

- In case of severe impact/shock (even when there is no visible damage) inform the fire brigade immediately; give information about the vehicle- state clearly that the vehicle is electric, inform about the type of potential fire and burning substance chemistry inside battery cells; the short circuit is possible due to broken battery insulation even after vehicle power shut off.
- Do not extinguish battery fire. The risk of toxic vapour inhalation and severe burns is too high.
- Remain at the disposal of the fire brigade when they arrive.

### Fire in a storage area

- Storage area should be prepared and equipped according to the local fire prevention inspector's prescription in compliance with effective local laws. The area is recommended to have C02, metal fire-ex powder or dry powder fire extinguishers (2 pieces, capacity – 6 kg), personal protective equipment: respirators, and dielectric insulating gloves.
- Battery fire danger is not recognized only by sparks and flames. Other potential fire symptoms are leaking fluids, increased temperature, and disturbing sounds such as bubbling or gurgling inside the battery.
- Remain upwind of the fire.
- · Call for medical help and provide first aid to the injured.
- Call the fire brigade and inform them about the accident; give them information about the vehicle- state clearly
  that the vehicle contains lithium-ion batteries, inform them about the type of fire and burning substance chemistry inside battery cells.
- Remain at the disposal of the fire brigade when they arrive.
- Do not extinguish battery fire yourself unless you have specialised equipment and attended the training. The risk of toxic vapour inhalation and severe burns is too high.
- To minimise damage to company goods and property before the fire brigade arrives, use personal protective equipment when extinguishing the fire (as prescribed by local fire prevention inspector, where applicable).
- Prevent the inhalation of toxic gas and carry out extinguishing actions from windward.
- · The fire should be extinguished by the fire brigade with suitable extinguishing media.

### Fire during charging

- Battery fire danger is not only recognized by sparks and flames, but potential fire symptoms are leaking fluids, increased temperature, and bubbling or gurgling sounds inside the battery.
- If it is safe to disconnect power from the battery (disconnect from the grid/ disable current flow in the battery) use an emergency power disconnect switch in the building/ area.
- Remain upwind of the fire.
- · Call for medical help and provide first aid to the injured.
- Call the fire brigade and inform them about the accident; give them information about the vehicle- state clearly that the vehicle is electric, inform them about the type of fire and burning substance chemistry inside battery cells.
- Remain at the disposal of the fire brigade when they arrive.
- Do not attempt to extinguish a battery fire unless you are trained and equipped to do so.
- . The risk of toxic vapour inhalation and severe burns is too high.
- To minimise damage to company goods and property before the fire brigade arrives use prescribed by local fire prevention inspector personal protective equipment when extinguishing a fire. Prevent the inhalation of toxic gas and carry out extinguishing actions from windward.
- The fire should be extinguished by the fire brigade with suitable extinguishing media.

### Additional advice for firefighters

- Use self-contained breathing apparatus.
- · Wear a fully protective suit.
- · Cool unbroken containers at risk with a water spray jet.
- Fire residues and contaminated firefighting water must be disposed of in accordance with local regulations.

### Storage of damaged batteries

After the accident, immediately isolate the battery in a safe place. If the battery starts to emit an unusual smell, develop heat, change shape/geometry, emit disturbing sounds, or behave abnormally it may indicate a problem.


In this case, the battery must be given special attention. Additionally, damaged batteries must be stored in a well-ventilated area and protected from third-party access. They must be separated from other batteries. If there is a fire hazard involved, inform the fire brigade and the manufacturer immediately. The storage area must be equipped with a fire extinguisher applicable to this battery. For safety reasons damaged batteries/cells should not be stored at the user's facilities. They should be disposed of in compliance with applicable regulations. It is also recommend storing the battery after the fire in a special crate in a quarantine zone.

### 7. In case of Submersion

### Floodwater or Fording.

Maximum wading depth under normal usage should not exceed 32cm.





### Deeper Immersion. (Depths greater than 33cm)

If the depth of water exceeds 33cm or is unable to be determined, seek an alternative route.

Travel in deeper water can cause damage to critical systems including, but not limited to, HV systems, and could lead to dangerous exposure to high voltages as well as causing breakdowns.

If the vehicle has been fully immersed in water for longer periods, contact Alexander Dennis for details on how to deal with the battery packs.

In the event of submersion (water is above the entrance ramp or over the rear bumper), proper PPE gear **is required** with a **MINIMUM ARC FLASH RATING OF 8CAL/CM2** before approaching the rear of the vehicle.

If the HV Battery is submerged or partially submerged, a voltage hazard exists at the batteries and may exist between HV energized components. Avoid contact with HV components, cabling, or service disconnects on a submerged vehicle.

The front and sides of the vehicle do not pose a HV risk if partially submerged.

The vehicle should be retrieved from the water before other work is performed. Water levels below the bottom of the vehicle (less than 30cm) should not pose any HV risk.

- 1. Assess vehicle for risks.
- 2. Shutdown the vehicle by pushing the emergency stop switch on the driver's side console to the STOP position. (See page 11)
- 3. If accessible disconnect the 24 VDC Batteries, located behind the battery access door below the driver's cab. (See page 12)
- 4. Avoid contact with High Voltage (HV) components.
- 5. Attend to any first aid needs.
- 6. Access to passengers can be gained through the entrance and exit doors, or side windows.



Stop Bus

### **⚠** DANGER

High Voltage Cables are routed within the rear compartment and under the vehicle. If these cables become damaged or exposed during an accident, they may remain live. Ensure the High Voltage system is disabled using the High Voltage Interlock switch, after recovering the vehicle from the water, before working in the area of damaged cables.

### Storage following immersion:

The vehicle should be stored in a safe, covered location.

The bus should be locked out to prevent it being powered-up until all systems have been checked and certified safe to use by a qualified and approved engineer.

All water should be allowed to drain away and the vehicle dried thoroughly before any attempt is made to restore power to any system.

### 8. Towing / Transportation / Storage

When towing the vehicle, always follow the correct towing procedure as detailed below.

### **Towing Preparation**

### When towing, the following functions are not available:

- 1. Power assisted steering
- 2. Compressed air supply
- 3. Recharging of the 24Volt vehicle battery

### Preparations before towing the vehicle

- 1. Select neutral gear and apply the parking brake.
- 2. Remove both half-shafts (see over for details).
- 3. Attach vehicle to tow truck.
- 4. Release the parking brake.
- 5. Turn off the ignition and master switches to power-off the bus.
- 6. Where applicable, turn off the 24V battery disconnect switch within the front battery compartment.
- 7. Disconnect the HV system by removing the Manual Service Disconnect (MSD) plugs at the rear.
- 8. Vehicle tow can now proceed.

Always keep road speed as low as possible and do not exceed 25MPH maximum speed at any time.

### **Disconnect High Voltage**

### **WARNING:** Trained personnel only

To access the **M**anual **S**ervice **D**isconnect plugs on the High Voltage Junction Box, open the rear drive bay door at the rear of the bus.



**1:** Press the lower part of the ignition switch to turn off the bus.

2: Press and release the master

switch to turn off the main power.

Switch will flash while the bus

Switch will flash.

shuts down.




Turning off the bus



Do not disturb the MSD plugs if the vehicle is on charge. Stop and remove charge supply before touching.

Failure to do so may result in danger to life or damage to equipment

On both MSD plugs, release the locking tabs before lifting the lever to 90°, then pull the plugs out of the High Voltage Junction Box.




### **Accessing Towing Connections**

To access the towing eye socket and compressed air charge coupling, open and remove the front panel. Store the panel safely inside the bus.

The towing eye should be screwed into the tapped socket in the front crossmember.


An air coupling is located on the front of the vehicle to provide air to the braking system during the tow.



Open and lift panel out and away from the clips







Connect rigid tow bar to OFFSIDE towing eye only

For rigid bar towing only the OFFSIDE eye must be used, as indicated, to prevent damage to the front components.

The vehicle may be towed using both front towing points and an A-Frame. The vehicle may also be recovered by a lifted or suspended front end tow.

### Releasing the park brake

### **∆WARNING**:

In this condition the parking brakes are completely inoperative. Wheels MUST be chocked to prevent the vehicle from rolling.


The electronic parking brake will NOT be disengaged with an external air supply to the air charge point, so manual release of the spring brake actuators will be necessary

Access to the drive axle actuators is via an access panel on the floor between the rear seats over the rear axle. Use an allen wrench to remove the panel. This gives access to the top of the brake actuators.

DESCRIPTION OF THE PROPERTY OF

Use a 24mm spanner to wind the actuators off to release the brakes. When the vehicle is towed, the rear half-shafts must be removed to prevent damage to the axle or drive motor.

Alternatively the propshaft may be removed or the rear axle lifted off the road



## Removing drive axle half-shafts

### **△WARNING**:

Proper consideration must be given to traffic conditions and the danger from passing traffic fully assessed and any necessary precautions taken before attempting to remove half shafts.

When towing, both axle half-shafts MUST be removed to prevent any damage to the axle or drive motor. When half-shafts are removed, the open axle ends must be temporarily plugged to prevent loss of oil.

The removed shafts should be stored safely inside the bus.

Make sure to identify which shaft came from which side. Do not swap over.

For towing purposes, there is no need to remove the wheels.

Loosen screws on the flange shaft and pull out the half shaft.

Be prepared to catch any outfall of oil from the axle during this process.

Note: When the half shafts are removed, plug or cover both hubs.


# Suspended Towing

When carrying out a suspended tow in reverse, it is important to lock the steering in the "straight-ahead" position to prevent uncontrolled movement of the steering gear and front axle steering components.

The vehicle should be not be lifted beyond the figures given when using a suspended tow;

Front lift angle not to exceed 7.6°

Rear lift angle not to exceed 7.2°




### After Towing

### **△WARNING**:

When the tow procedure is complete, the parking brakes must be wound back on or the wheels chocked to prevent the bus from rolling away.

See the service manual for correct procedures and torques when refitting the half-shafts to the axle. It is important to check the oil level of the axle after any towing procedure where the hubs are disturbed.

Ensure the drive shafts are installed on the correct side: See service manual



### 8. Towing / Transportation / Storage

### Vehicle Storage.

When storing the vehicle following a fire or crash follow the below instructions.

### Procedure following a fire:

The vehicle should be quarantined in a safe, covered location, away from other vehicles.

Monitor the battery areas with thermal equipment for up to 48 hours to ensure there is no spontaneous reignition



All HV systems should remain disconnected and locked off until fully inspected by a qualified and approved engineer.

Any powder residue should be cleaned off to prevent any corrosion or other issues.

If water has been used to fight any fire, all affected systems must be thoroughly dried before any power is turned on.

### Procedure following immersion in water: (See also: Section 7)

The vehicle should be stored in a safe, covered location.

Do not power-up the bus until all systems have been checked and certified safe to use by a qualified and approved engineer.

All water should be allowed to drain away and the vehicle dried thoroughly before any attempt is made to restore power to any system.


### Suspended tow:

The vehicle should be not be lifted beyond the figures shown below when using a suspended tow;

Front lift angle not to exceed 7.6° Rear lift angle not to exceed 7.2°

(Figures apply to both 1- and 2-door variants)

When carrying out a suspended tow in reverse, it is important to lock the steering in the "straight-ahead" position to prevent uncontrolled movement of the steering gear and front axle steering components.



### 8. Towing / Transportation / Storage

When storing the vehicle, always follow the correct storage disconnection procedure as detailed below.



### **Vehicle Storage Up To 6 Months**


Alexander Dennis recommends the following actions when storing new vehicles for a period of up to 6 months. NOTE: It is required that the vehicle Rechargeable Energy Storage System SOC is not less than **30%** prior to long term storage commencing.

Stage 1: Shutdown and Isolate 24v Battery.

### **ALWAYS** engage the parking brake before leaving the cab.

After operation remember to:

- Select 'Neutral'
- Apply the parking brake.



Turning off the Bus:

- 1: Press the lower part of the ignition switch to turn off the Bus. Switch will flash.
- 2: Press and release the master switch to turn off the main power. Switch will flash and the rundown sequence begins.



### **Short Term Vehicle Storage**

### 24V Battery: Disconnect and Monitor

When it is necessary to store the vehicle for longer than 48 hours it is important to make sure the correct storage procedures are followed. Follow the 24v battery disconnection procedure.

Alexander Dennis recommend regular testing of the 24v battery system in order to maintain optimum battery performance and to reduce vehicle downtime. It is recommended that an industry suitable tester be used to determine the condition of the batteries on a regular basis.

The tester must be correctly suited to the task of testing an SLI lead-acid battery with up to 230Ah and 1200A CCA.

### **24v Battery Disconnection**

### △ WARNING: DO NOT disconnect the batteries while the bus is running

Battery access is via an access door at the front, below the driver's cab.

When the Timeout warning light turns off, it is safe to rotate the Battery Disconnect Switch to the off position. Lift the flap and rotate the 24v Battery Disconnect switch at the rear of the tray to isolate the 24v supply.

### If the Battery Disconnect Switch is unavailable:

Lift and secure the access door, release the antiluce fasteners, then slide the tray out to access the battery connectors and remove the negative connection.

Secure cable to prevent accidental re-connection.





### **Longer Term Vehicle Storage**

### **Traction Battery: Monitor SOC**

Where the storage period is likely to exceed 30 days, in addition to the 24v monitoring, the HV batteries will also require checking as follows:

The vehicle should be stored with a traction battery SOC of **100%** at the start of storage period. Li-lon SOC must be returned to full every 3 (three) months.

Optimum temperature for storage is between 0°C and +25°C (Maximum limits -35°C / +55°C)

Humidity should not exceed 80%. **NOTE:** Higher temperatures will decrease battery service life. Before returning the bus to use, the batteries should be subject to an inspection and a "service recharge":

- Power-up the bus, then reduce the SOC to below 20%, park and shut off the bus for a minimum of 1 hour.
- Return to the charging station and carry out full recharge procedure.

### **Safety Note**

Do not store vehicle if any battery pack is damaged, this must be investigated and rectified immediately. Storage area should be equipped with fire extinguisher (CO2 or Dry Powder type)



### 9. Important Additional Information

Rear Impact Detection Sensor.

### Following a collision:

In the case of a rear impact, the vehicle has a rear-mounted impact sensor that is triggered by excess G-forces.

The vehicle will not turn on and will display "Emergency Shutdown Active" symbol on the dashboard



The vehicle will display "Rear Impact Detection Sensor" symbol on the dashboard



There may be a text display in the centre of the screen showing the shutdown is active, and the reason. Use the I-Button to scroll through the messages.





The Rear impact sensor must be reset before the vehicle will turn on.

It is important to ensure there is no damage to any of the HV systems before the sensor is reset in order to prevent any accidental exposure of personnel to high voltages.

The sensor is located at the rear of the vehicle, inside the drive bay.

Access to reset the switch is via the rear drive bay door.

CAUTION: Do not attempt to access this area if there is any damage to any part of the HV system in the drive bay. Damaged insulation or HV components may present an electrocution risk.





To reset the crash sensor, push the button on the top of the unit.

### 10. Explanation of Pictograms Used

### 1. Propulsion Identification



Li-Ion / LFP Battery - Electric bus

Model designation display not guaranteed.

### 2. Immobilisation / stabilisation / lifting



Suspension controls in driver's switch area.

Safe lifting points.

### 3. Disable direct hazards / safety regulations



Disconnect High Voltage.



Disconnect Low Voltage.


### 4. Access to the occupants





Door access control - entrance and exit doors.







Steering wheel control on driver's footplate.

### 5. Stored energy



























### 6. In case of fire











### 7. In case of submersion





As for Section 3: Disable Direct Hazards

Follow all recommended safety routines once out of the water.

### 8. Towing / transportation / storage



Disconnect High Voltage.



Disconnect Low Voltage.

### Extra information.

The appendix to this document contains extra information (as Safety Data Sheets) as follows:

- 1. HV Battery pack info
- 2. Hydraulic steering oil (Fuchs Titan ATF 4000)
- 3. R407C refrigerant (BOC gasses)
- 4. Valvoline coolant (Valvoline OEM ADV48)
- 5. Flooded Lead acid 12V battery (Varta)

This document covers only those models listed on the front cover. It should be regarded as part of the product and retained with the vehicle. At the time of resale it should be passed on to any subsequent owner. Where the manual lists the specifications for several models, some of the items covered may not apply to your vehicle.

If any doubt exists please do not hesitate to contact Alexander Dennis who will be pleased to offer technical assistance.

We would like to point out that non-Alexander Dennis parts have not been approved by Alexander Dennis and we cannot certify the suitability nor the safety of such parts. Alexander Dennis is not liable for any damage caused by the use of non-Alexander Dennis parts.

### Disclaimer

This manual applies to the vehicle model(s) stated on the front cover and is deemed to be part of the vehicles supplied by Alexander Dennis.

This manual may not be shared with third parties without our prior approval.

This manual should be kept with the relevant vehicle(s) and if the vehicle(s) are sold, it should be passed on to any subsequent owner. Where the manual includes specifications for different vehicle models, some items may not apply to your specific vehicle.

Use of and access to AD24 and AD Connect is subject to our Terms of Service.

All intellectual property rights in this manual are owned by us and our licensors. We and our licensors reserve all our intellectual property rights (including, but not limited to, all copyright, trademarks, domain names, design rights, database rights, patents, and all other intellectual property rights of any kind) whether registered or unregistered anywhere in the world.

No part of this manual may be translated, copied, modified, adapted, reprinted or reproduced or utilised in any material form either in whole or in part or by any electronic, mechanical or other means, now known or invented in the future, including photocopying and recording, or in any information storage and retrieval system, without prior permission in writing from Alexander Dennis.

This manual does not apply to any non-Alexander Dennis parts or components. Any references in this manual to any non-Alexander Dennis parts or components is for information only.

All liability of Alexander Dennis in connection with this manual (regardless of whether such liability arises in tort, contract or in any other way and whether or not caused by negligence or misrepresentation) for any loss or damage, costs, expenses, or other claims (including but not limited to special, direct, indirect, or consequential loss or damage) is excluded to the fullest extent permitted by law.



Alexander Dennis Limited, registered in Scotland (Company Number SC268016) with its registered office at 9 Central Boulevard, Larbert, FK5 4RU, United Kingdom

Document Ref: 4020-2 Enviro200EV TfL ERG Doc Standard: ISO 17840-3 Date: Sep 2025

# Appendix of extra information.

### **SDS** information

1.	HV Battery pack info	Page 3 - 11
	Hydraulic steering oil (Fuchs Titan ATF 4000)	-
3.	R407C refrigerant (BOC gasses)	Page 26 - 43
4.	Valvoline coolant (Valvoline OEM ADV48)	Page 46 - 68
5.	Flooded Lead acid 12V battery (Varta)	Page 70 - 80



### 宁德时代新能源科技股份有限公司

### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

### 1. Product and enterprise identification

Product name	Lithium Ion Battery	CATL model name	L302C01
Manufacturer	Contemporary Amperex Technology Co., Limited	Estimated weight	217Kg
Rated capacity	302Ah	Rated voltage	115.92V
Address	No.2 Xingang Road, Zhangwan Town, Jiaocheng District, Ningde City, Fujian Province, China, 352100		
Contact number	+86-593-2583668		

### 2. Overview of Hazards

### 2.1 Overview of Emergency Situations

The lithium ion battery described in this safety technical specification is sealed, can withstand the temperature and pressure during normal use, and has no risks such as fire, explosion, leakage of dangerous chemicals, etc. Only when the integrity of the battery is damaged or the battery is subjected to mechanical, thermal or electrical abuse can the materials contained in the battery pose a risk.

### 2.2 Hazard Categories

### See section 3 for component information

· Label element

N/A.

· Hazard statement

N/A.

:: Precautionary statements

N/A.

2.3 Health hazards: Battery electrolyte may irritate skin and eyes. If the battery breaks, the toxic gas volatilized by electrolyte will seriously damage the eyes, stimulate the respiratory tract and even cause respiratory allergy.

### 3. Composition information

### 3.1 Battery pack composition

Composition	%/wt.
Battery outer box, metal bracket and control system	35-45
Battery (see Table 3.2 below for battery composition)	55-65

### 3.2 Battery Composition Table

Raw materials or ingredients	CAS No./EC No.	Hazard pictogram and hazard	%/wt.	ĺ
------------------------------	----------------	-----------------------------	-------	---



### 宁德时代新能源科技股份有限公司

### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

		description	
Consult its	CAS # 7782-42-5	Not classified	7-25
Graphite	EC # 231-955-3		
C-114 1/41 :	CAS # 182442-95-1	& Carc. 1B, H350;	5 40
Cobalt lithium manganese nickel oxide	EC # 695-690-9	Acute Tox. 2, H330	5-40
maly(vinylidana flyanida)	CAS # 24937-79-9	Not classified	0-5
poly(vinylidene fluoride)	EC # 607-458-6	Not classified	0-3
Carbon	CAS # 1333-86-4	Not classified	0-2
Carbon	EC # 215-609-9	Not classified	0-2
Copper	CAS # 7440-50-8	Not classified	10-12
Соррег	EC # 231-159-6	Not classified	10-12
Aluminum	CAS # 7429-90-5	Not classified	3-5
	EC # 231-072-3	Titot Glassifica	
Carboxymethylcellulose sodium	CAS # 9004-32-4	Not classified	0-5
Carboxymemyreendiose sodium	EC # 618-378-6	Ivot classified	0-3
Electrolyste	NA	See 3.3 Table of Main Substances of	3-20
Electrolyte	INA	Electrolyte	

### 3.3 Electrolyte Composition Table

Raw materials or ingredients	CAS No./EC No.	Hazard pictogram and hazard description	%/wt.
Lithium hexafluorophosphate	CAS # 21324-40-3 EC # 244-334-7	Acute Tox. 3, H311 Skin Corr. 1A, H314 Acute Tox. 4, H302 STOT RE 1, H372	5-15
Dimethyl carbonate	CAS # 616-38-6 EC # 210-478-4	♦ Infammable, H225	0-15
Ethylene carbonate	CAS # 96-49-1 EC # 202-510-0	<ul><li>♠ Eye Irrit. 2, H319</li><li>♠ Acute Tox. 4, H312</li></ul>	0-15
Diethyl carbonate	CAS # 105-58-8 EC # 203-311-1	♦ Flam. Liq. 3, H226	0-15
Methyl ethyl carbonate	CAS # 623-53-0 EC # 613-014-2	<ul><li>♦ Infammable, H225</li><li>♦ Skin Irrit. 2, H315</li></ul>	0-15

### 4. First aid measures

- 4.1 Intake: The ingredients of the battery can cause severe chemical burns to the mouth, esophagus and gastrointestinal tract. If the battery or disassembled battery is ingested, do not induce vomiting or eat food or drink. Seek medical attention immediately.
- 4.2 Inhalation: The ingredients in the battery may cause respiratory allergy, and inhalation of steam may cause upper respiratory tract and lung allergy. Breathe fresh air and seek medical advice immediately.
- 4.3 Skin contact: The ingredients in the battery may cause skin allergies or chemical burns. In case of



### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁德市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

contact, remove contaminated clothing and wash skin with soap and water. In case of chemical burns or persistent irritation, seek medical advice immediately.

4.4 Eye contact: The ingredients in the battery may cause severe allergies and chemical burns. In case of contact, immediately open the upper and lower eyelids and rinse the eyes with clear water for more than 15 minutes until there is no chemical residue. Then seek medical advice immediately.

#### 5. Fire protection measures

5.1 Fire extinguishing agent: Water or water mist, dry powder or carbon dioxide fire extinguisher

#### 5.2 Particular Hazards

- 1. The voltage of a single cell in each box is 2.8~4.25V.
- 2. The electric box may fall and squeeze during transportation. If the internal battery core is punctured, metal short circuit, immersion, etc., it will lead to electric shock or fire.
- 3. When the electrolyte in the battery leaks, there will be the risk of explosion. In addition, improper disposal of electrolyte will also cause environmental pollution.
- 4. Dangerous decomposition products (such as electrolyte vapor or other harmful vapor) may be produced under the condition of battery ignition, overheating or overvoltage, and the vapor density is generally heavier than air, which will spread on the ground and may contact the ignition source through ventilation.
- 5.3 Precautions and Protective Measures for Fire Extinguishing
- 1. Give an alarm immediately when smoke or burning is found in the box. 2. Wear protective equipment, including respirators and masks. If water is used, raincoats, rain boots and insulating gloves should also be included. 3. Cut off the power. 4. Use solid fire extinguishing equipment. It is recommended to use fire extinguishing equipment in the following order: water or water mist, sand, fire blanket, dry powder and carbon dioxide fire extinguisher. 5. Exhaust smoke through fan or air circulation. 6. Dry and neutralize. Dry by fan. If water is used, neutralize it with calcium hydroxide. Dry by fan.

### 6. Accidental Release Measures

If the internal materials of the battery leak, the relevant leakage emergency measures are as follows:

6.1 Emergency procedures: Evacuate personnel from polluted areas to safe areas quickly, isolate them, and strictly restrict access. Cut off the fire source and leakage source as much as possible. Personal protective measures and protective equipment: It is recommended that emergency personnel wear self-contained positive pressure respirator and fire protection clothing, and do not directly contact with leakage.



### Contemporary Amperex Technology Co. ,Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

6.2 Environmental protection measures: When the battery pack is in water, there is a risk of weak electric shock; Hydrogen will be produced when electrolyzing water, so ventilation must be kept to prevent hydrogen from accumulating and exploding in confined space. If possible, take the battery or module out of the water and report to the local police.

#### 6.3 Electrolyte cleaning method:

Minimal leakage: Absorbed with sand vermiculite or other inert materials collected and transported to an open area for burial evaporation or incineration.

Large amount of leakage: build a dike or dig a hole to accommodate it. Cover with foam to reduce steam hazards. Transfer to tank truck or special collector with explosion-proof pump, and recycle or transport to waste treatment site for disposal.

#### 7. Operational disposal and storage

The battery should be stored in a ventilated and cool place (below 30 °C), away from moisture, and there is enough space between the battery and the wall; Batteries should be kept away from heat sources, open flames, food and beverages; Do not store batteries above 55 °C or below-30 °C. Storing the battery at high temperature will shorten the life of the battery, while storing the battery at higher temperature (such as 100 °C) may lead to the emission of flammable liquids and gases in the battery; Batteries should be kept away from strong oxidants and acids.

#### 7.1 Operational Considerations

- 1 Do not carry out excessive physical impact or vibration on the battery.
- 2 Short circuit should be avoided. A long short circuit can cause the battery to lose energy quickly, which can generate enough heat to burn the shell.
- 3 The sources of short circuit include the random placement of batteries in bulk containers or various metal objects used in battery assembly on equipment. In order to minimize the risk of battery short circuit, battery protection measures should be provided during battery transportation and storage.
  - 4 Do not disassemble or deform the battery.
  - 5 When the battery is broken, do not contact it with water.

#### 7.2 Storage Considerations

- 1 When the lithium ion battery is stored for a long time, its charging capacity should be between 25% and 75%.
  - 2 It should be stored in a dry, cool and well ventilated area.
  - Excessive temperature will cause a series of problems, such as leakage or rust.
  - Do not put the battery in an open flame.



### Contemporary Amperex Technology Co. ,Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

8. Contact control and personal protection

8.1 Occupational Exposure Limits: N/A

8.2 Biological Limit: N/A

8.3 Monitoring method: N/A

8.4 Engineering control: Engineering control is not required under normal operation. In case of extrusion or collision, it is judged that there may be electric leakage, and insulating gloves are needed. In case of electrolyte leakage, increase ventilation and use self-contained full-face breathing equipment.

8.5 Personal Protective Equipment: Needed in case of battery fire or explosion, without protection when the battery is in normal use.

Respiratory system protection: self-contained full-face breathing equipment.

Hand protection: Insulated gloves.

Eye protection: self-contained full-face breathing equipment.

Skin and body protection: Chemical protective clothing.

#### 9. Physical and chemical properties

Status	solid
pН	N/A
Color	N/A
Odor	none
Flash point	N/A
Explosion limit	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility	Insoluble in water
Specific gravity	N/A
density	N/A
Melting point	N/A
Freezing point	N/A
Status	solid

### 10. Stability and reactivity

10.1 Stability: Stable under normal conditions.

10.2 Reactivity: When the battery is exposed to high temperature, extrusion, deformation or external short circuit may lead to the discharge of harmful gases and volatile organic compounds. When the battery breaks, it will react with water to form hydrogen fluoride gas.



### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

10.3 Conditions to be avoided: N/A10.4 Prohibited Compounds: N/A

#### 11. Toxicological information

There is no available data for the product itself, and the information of its internal battery materials is as follows:

- 11.1 Acute toxicity: No information is currently available.
- 11.2 Irritation: The electrolyte contained in the battery will irritate the eyes, and if it comes into contact with the skin or mucous membrane for a long time, it will also cause irritation;
- 11.3 Sensitization: The electrolyte contained in the battery may stimulate the nervous system of respiratory organs.
- 11.4 Carcinogenicity: No information is currently available.
- 11.5 Reproductive toxicity: No information is currently available.
- 11.6 Teratogenicity: No information is currently available.
- 11.7 Mutagenicity: No information is currently available.
- 11.8 Specific target organ systemic toxicity: No information is currently available.

#### 12. Ecological information

If the battery is to be scrapped, it should be selected and disposed of by a professional company. After the battery is properly handled, it will not cause harm to the environment. However, the internal components of the battery pack should not be allowed to enter the ocean, and should not be discharged into rivers, waste water or groundwater.

- 12.1 Ecotoxicity: No information is currently available.
- 12.2 Persistence and degradability: No information is currently available.
- 12.3 Biological abs or bioaccumulation: No information is currently available.
- 12.4 Migration in soils: No information is currently available.

#### 13. Waste disposal

- 13.1 Waste chemicals: The battery should be fully discharged before disposal. Battery poles should be covered to prevent short circuit. Batteries need to be disposed of in accordance with applicable laws.
- 13.2 Contaminated packaging materials: Dispose of according to national or local laws and regulations.
- 13.3 Precautions for abandonment: Dispose of according to national or local laws and regulations.

#### 14. Transport information



### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

Land transportation: International Carriage of Dangerous Goods by Road (ADR), Regulations on International Carriage of Dangerous Goods by Rail (RID).

Maritime transport: International Maritime Dangerous Goods Code (IMDG CODE).

Air transport: International Civil Aviation Organization-Technical Directive for Safe Transport of Dangerous Goods by Air (ICAO-TI) and International Air Transport Association-Dangerous Goods Regulations (IATA-DGA).

Inland waterway transport: Regulation on the Safety Supervision and Control of Dangerous Goods on Ships, European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN).

Others: Model Regulations of the United Nations Recommendations on the Transport of Dangerous Goods (TDG), Manual of Tests and Criteria of the Model Regulations of the Recommendations on the Transport of Dangerous Goods

Made of two new out	Land transportation	Sea transportation	Shipping		
Mode of transport	(ADR/RID)	(IMDG)	(ICAO/IATA)		
UN number	3480/3481	3480/3481	3480/3481		
Shipping name	Lithium ion battery pack	Lithium ion battery pack	Lithium ion battery pack		
Transportation hazard level	9	9	9		
Packaging category		II			
Packaging requirements	/	P 903	PI 965-967		
Label	UN 3480 For mass information, planes call				
Matters needing attention	<ol> <li>The transported batteries need to pass the UN38.3 experimental test.</li> <li>The package shall withstand a 1.2 m drop test of any orientation without damaging the batteries in the package, changing the position of the batteries in the package so that they contact each other and no batteries leak out of the package.</li> <li>Cells must not be damaged or mishandled. If they are damaged, they must be isolated, inspected and repackaged.</li> <li>Comply with the special provisions of international regulations on the packaging of lithium batteries or lithium battery packs.</li> </ol>				

## 15. Regulatory information

### 15.1 United States Federal Regulations

Occupational Safety and Health Act (OSHA): Employers/enterprises must ensure that lithium batteries, chargers and lithium-ion-related equipment used in the workplace are tested according to appropriate testing



### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

### MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

standards (such as UL 2054) and certified by testing institutions with NRTL (Nationally Accredited Testing Laboratory) qualification.

Toxic Substances Control Act (TSCA): This product is not listed.

Clean Air Act (CAA): This product is not included.

Clean Water Act (CCW): This product is not listed.

### 15.2 Canadian Regulations

Workplace Hazardous Goods Information System (WHMIS): This product is not included.

Hazardous Products Act (HPA): This product is not listed.

Canadian Environmental Protection Law (CEPA): This product is not listed.

#### 15.3 German regulations

Regulations on facilities for treating harmful substances to water (AwSV): The hazard grade of electrolyte to water of this product is WGK2 (hazardous to water).

### 15.4 EU Regulations

It does not contain substances on REACH candidate list.

No REACH appendix XVII/XIV substances.

### 15.5 International Regulations

Australian List of Existing Chemicals (AICS): This product is not included.

List of Existing Chemical Substances in China (IECSC): This product is not listed.

List of Existing Chemical Substances in Japan (ENCS): This product is not listed.

List of Existing Chemical Substances in Korea (ISHL): This product is not listed.

New Zealand List of Existing Chemicals (NZLOC): This product is not listed.

### 16. Other information

#### 16.1 Charging

The battery can be recharged for many times. Please use the original battery charger. Do not use modified or damaged battery chargers. When the charging exceeds the specified charging time, the charging can be stopped to prevent the battery from overcharging. The charging temperature should be at-20 C-45 C (from the safety point of view, there is no experience value during fast charging), and there is normal heating phenomenon during battery charging.

# 16.2 Charging Voltage and Current

When the voltage exceeds the specified value, it is limited by the internal protection circuit of the battery. If the protection circuit is damaged, please stop using it. Please charge and discharge at the specified voltage and current. If the battery voltage drops below the specified minimum voltage, please stop using it.

### 16.3 Warning



### Contemporary Amperex Technology Co., Limited

No.2 Xingang Road, Zhangwan Town, Jiaocheng Distric, Ningde City, Fujian Province, P.R of China, 352100

中国福建省宁湾市蕉城区漳湾镇新港路 2 号 352100

# MATERIAL SAFETY DATA SHEET

物料安全技术说明书

Issue: 2024-A Doc No.: 2024-A-312 Issue Date: 11/9/2024

Use the charger provided by the equipment manufacturer and use it according to the operation instructions. It is forbidden to turn on the battery, close to the fire source, and short circuit, which may cause fire, explosion, leakage and personal injury.

#### 16.4 Declaration

The information contained here was completed without any authorization. This information is only used as a reference, and users should customize independent systems according to the complete and reliable information they actually collect, so as to ensure proper use and ensure the safety and health of employees and customers.

#### 16.5 Revise version number

CATL V2 2024/3/25



# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: TITAN ATF 4000

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS GERMANY GmbH

Friesenheimer Str. 19 68169 Mannheim

Telephone: +49 621 3701-0 (ZENTRALE)

Fax: +49 621 3701-570

Contact for request of safety data sheets

E-mail: Automotive lubricants automotive-FLG@fuchs.com

Industrial lubricants industrie-FLG@fuchs.com

Telephone: +49 621 3701-0 (ZENTRALE)

Informing department for safety data sheets

E-mail: produktsicherheit-FLG@fuchs.com

**1.4 Emergency telephone number:** +49 621 3701-0 (Mo - Fr 08:00 - 16:00 Uhr)

**SECTION 2: Hazards identification** 

#### 2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

**Environmental Hazards** 

Chronic hazards to the aquatic Category 3 H412: Harmful to aquatic life with long lasting

environment effects.

**Hazard summary** 

Physical Hazards: No data available.

#### 2.2 Label Elements

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022 SDS DE - EN - 00000000600631963

Appendix Page: 14

AD Pub N°. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

1/10



Product name: TITAN ATF 4000

**Hazard Statement(s):** H412: Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

**Prevention:** P273: Avoid release to the environment.

**Disposal:** P501: Dispose of contents/container to an appropriate treatment and

disposal facility in accordance with applicable laws and regulations,

and product characteristics at time of disposal.

**2.3 Other hazards:** By handling of mineral oil products and chemical products no particular

hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the envi-

ronment without control.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**General information:** Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentration *	REACH Registra- tion No.	Notes
Methacrylate copolymer	Confidential	1,00% - <5,00%	Confidential	
Base oil, low viscous	EINECS: 265-158-7	1,00% - <10,00%	01-2119487077-29	
Alkyl amine	EC: 620-540-6	0,25% - <1,00%	01-2119510877-33	
prim. alkanolamine ether	EC: 939-485-7	0,001% - <0,10%	01-2119974116-35	

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# Classification

Chemical name	Identifier	Class	ification
Methacrylate copolymer	Confidential	CLP:	Eye Irrit. 2;H319
Base oil, low viscous	EINECS: 265-158-7	CLP:	Asp. Tox. 1;H304
Alkyl amine	EC: 620-540-6	CLP:	Skin Corr. 1C;H314, Eye Dam. 1;H318, Aquatic Acute 1;H400, Aquatic Chronic 1;H410, Acute Tox. 4;H302; M-Factor (aquatic acute): 10; M-Factor (aquatic chronic): 1
prim. alkanolamine ether	EC: 939-485-7	CLP:	Acute Tox. 4;H302, Skin Corr. 1B;H314, Eye Dam. 1;H318, Aquatic Acute 1;H400, Aquatic Chronic 1;H410; M-Factor (aquatic acute): 100; M-Factor (aquatic chronic): 1

CLP: Regulation No. 1272/2008.

### specific concentration limit

Chemical name		specific concentra- tion limit		Category	Hazard state- ments
Methacrylate copolymer	Confidential	>= 75 %	Serious eye irritation	2	H319

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022 SDS DE - EN - 000000000600631963

AD Pub N°. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

2/10

Appendix Page: 15

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



Product name: TITAN ATF 4000

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

### **SECTION 4: First aid measures**

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and

delayed:

May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing me-

dia:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-

Unsuitable extinguishing

media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mix-

ture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting proce-

dures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter

drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

Revision Date: 14.09.2022 Version: 3.1 Print date: 18.09.2022

SDS DE - EN - 000000000600631963

Appendix Page: 16 AD Pub Nº. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

3/10



Product name: TITAN ATF 4000

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures:

In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning

up:

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

### **SECTION 7: Handling and storage:**

7.1 Precautions for safe handling:

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities:

Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

7.3 Specific end use(s):

Not applicable

**Storage Class:** 10, Combustible liquids

#### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control Parameters

**Occupational Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Base oil, low viscous - Respirable fraction.	MAK	5 mg/m3	Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as amended (2017)

### 8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Print date: 18.09.2022 SDS DE - EN - 000000000600631963

4/10

Appendix Page: 17

Revision Date: 14.09.2022

Version: 3.1



Product name: TITAN ATF 4000

General information: Wash hands before breaks and after work. Use personal protective equip-

ment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad-

hered to inhandling the chemicals or the mineral oil products.

**Eye/face protection:** Safety glasses (EN 166) recommended during refilling. Avoid contact with

skin and eyes. Goggles/face shield are recommended. If risk of splashing,

wear safety goggles or face shield.

**Skin protection** 

**Hand Protection:** Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufactur-

er of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pock-

ets. Wear suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the workplace. Avoid breathing va-

pour/ aerosol.

Thermal hazards: Not known.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot-

wear that cannot be cleaned.

**Environmental Controls:** No data available.

### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

**Appearance** 

**Flash Point:** 

Physical state: liquid Form: liquid Color: Red

Odor: Characteristic

**pH:** substance/mixture is non-soluble (in water)

Freezing point: not determined

Boiling Point: Not applicable

**Evaporation Rate:**Not applicable for mixtures

Flammability (solid, gas): not determined

Flammability Limit - Upper (%)-: Not applicable for mixtures

Revision Date: 14.09.2022 Version: 3.1 Print date: 18.09.2022

190 °C

SDS DE - EN - 000000000600631963

Appendix Page: 18

AD Pub N°. 2982-4 ERG - © Alexander Dennis 2024 - All rights reserved

5/10



Product name: TITAN ATF 4000

Flammability Limit - Lower (%)—:

Vapor pressure:

Relative vapor density:

Not applicable for mixtures

0,86 g/ml (15,00 °C)

Solubility(ies)

Solubility in Water: Insoluble in water
Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Autoignition Temperature:not determinedDecomposition Temperature:not determinedKinematic viscosity:35,9 mm2/s (40 °C)

**Explosive properties:**Value not relevant for classification **Oxidizing properties:**Value not relevant for classification

Particle characteristics: Not applicable

9.2 Other information No data available.

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity:** Stable under normal use conditions.

**10.2 Chemical Stability:** Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

**10.4 Conditions to avoid:** Stable under normal use conditions.

**10.5 Incompatible Materials:** Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and oth-

er toxic gases or vapors.

### **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

## **Acute toxicity**

Oral

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s)

Base oil, low viscous LD 50 (Rat): > 5.000 mg/kg

Alkyl amine LD 50 (Rat): 1.350 mg/kg (OECD 401)

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022 SDS DE - EN - 000000000600631963

AD Pub N°. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

6/10



7/10

Product name: TITAN ATF 4000

**Dermal** 

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s)

Base oil, low viscous LD 50 (Rabbit): > 5.000 mg/kg

Inhalation

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s)

Base oil, low viscous LC 50 (Rat, 4 h): > 5 mg/l

Skin Corrosion/Irritation:

**Product:** Based on available data, the classification criteria are not met.

Specified substance(s)

Alkyl amine OECD 404 (Rabbit, 14 d):

Causes severe skin burns.

**Serious Eye Damage/Eye Irritation:** 

**Product:** Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization:** 

**Product:** Skin sensitizer: Based on available data, the classification criteria are not

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Specified substance(s)

Alkyl amine

No sensitizing effect (guinea pig); OECD 406

**Germ Cell Mutagenicity** 

**Product:** Based on available data, the classification criteria are not met.

Carcinogenicity

**Product:** Based on available data, the classification criteria are not met.

Reproductive toxicity

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** Based on available data, the classification criteria are not met.

**Aspiration Hazard** 

**Product:** Based on available data, the classification criteria are not met.

Other adverse effects: No data available.

Revision Date: 14.09.2022 Version: 3.1 Print date: 18.09.2022

SDS DE - EN - 000000000600631963

Appendix Page: 20 AD Pub No. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved



Product name: TITAN ATF 4000

### **SECTION 12: Ecological information**

### 12.1 Toxicity

**Acute toxicity** 

**Product:** Based on available data, the classification criteria are not met.

**Fish** 

Specified substance(s)

Alkyl amine LC 50 (Fish, 96 h): 0,1 mg/l (OECD 203)

Aquatic Invertebrates Specified substance(s)

Alkyl amine EC 50 (Water Flea, 48 h): 0,043 mg/l (OECD 202)

Chronic ToxicityProduct: Based on available data, the classification criteria are met.

Aquatic Invertebrates Specified substance(s)

Alkyl amine EC 10 (Water Flea, 21 d): 0,0107 mg/l (OECD 211)

Toxicity to Aquatic Plants Specified substance(s)

Alkyl amine EC 50 (Alga, 72 h): 0,0538 mg/l (OECD 201)

NOEC (Alga, 72 h): 0,0156 mg/l

### 12.2 Persistence and Degradability

Biodegradation

**Product:** Not applicable for mixtures

Specified substance(s)

Alkyl amine 63 % (28 d, OECD 301D) Readily biodegradable

12.3 Bioaccumulative potential

**Product:** Not applicable for mixtures

12.4 Mobility in soil:

**Product:** Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Other adverse effects:** Harmful to aquatic life with long lasting effects.

**Water Hazard Class** 

(WGK):

WGK 2: significantly water-endangering.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

**General information:** Dispose in accordance with all applicable regulations.

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022 SDS\_DE - EN - 000000000600631963

AD Pub N°. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

8/10

Appendix Page: 21



Product name: TITAN ATF 4000

**Disposal methods:** Discharge, treatment, or disposal may be subject to national, state, or local

laws.

### **European Waste Codes**

13 02 05\*: mineral-based non-chlorinated engine, gear and lubricating oils

### **SECTION 14: Transport information**

### ADR/RID

14.1 UN number or ID number: –

14.2 UN Proper Shipping Name: -

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s):

Hazard No. (ADR):

Tunnel restriction code:

14.4 Packing Group: -

14.5 Environmental hazards:

14.6 Special precautions for user:

#### **IMDG**

14.1 UN number or ID number: –

14.2 UN Proper Shipping Name:

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s): – EmS No.: –

14.3 Packing Group: -

14.5 Environmental hazards: –

14.6 Special precautions for user: -

#### **IATA**

14.1 UN number or ID number: -

14.2 Proper Shipping Name:

14.3 Transport Hazard Class(es):

Class: Non-dangerous goods

Label(s):

14.4 Packing Group: –

14.5 Environmental hazards: -

14.6 Special precautions for user:

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

# **EU Regulations**

EU. Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: none

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022

SDS\_DE - EN - 000000000600631963 9/10

Appendix Page: 22



Product name: TITAN ATF 4000

EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended: none

**National Regulations** 

**Water Hazard Class** 

(WGK):

WGK 2: significantly water-endangering.

15.2 Chemical safety as-

sessment:

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

**Revision Information:** Vertical lines in the margin indicate an amendment.

### Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H/12	Harmful to aquatic life with long lasting effects

H412 Harmful to aquatic life with long lasting effects.

**Other information:** The classification complies with the current EU lists; however, it has been

supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially simi-

lar mixtures" - Expert Judgement

**Revision Date:** 14.09.2022

**Disclaimer:** The data contained in this safety data sheet are based on our current

knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no sig-

nature.

Revision Date: 14.09.2022 Version: 3.1

Print date: 18.09.2022 SDS\_DE\_EN\_000000000000031963

AD Pub Nº. 2982-4 ERG - © Alexander Dennis 2024 – All rights reserved

SDS\_DE - EN - 00000000600631963

Appendix Page: 23

10/10



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 1/18

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

**Product name:** CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Other Name: Refrigerant R407C

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Industrial and professional. Perform risk assessment prior to use.

Refrigerant.

**Uses advised against** Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

BOC Telephone: 0800 111 333

Priestley Road, Worsley M28 2UT Manchester

E-mail: ReachSDS@boc.com

1.4 Emergency telephone number: 0800 111 333

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Physical Hazards

Gases under pressure Liquefied gas H280: Contains gas under pressure; may explode if

heated.

### 2.2 Label Elements



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

# CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 2/18



Signal Word: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

**Precautionary Statements** 

General None.

**Prevention:** None.

Response: None.

**Storage:** P403: Store in a well-ventilated place.

**Disposal** None.

Supplemental information

EIGA-0783: Contains fluorinated greenhouse gases EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards Contact with evaporating liquid may cause frostbite or freezing of skin.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Pentafluoroethane	C2HF5	17.9557%	354-33-6	01- 2119485636- 25	_	
Difluoromethane	CH2F2	38.1110%	75-10-5	01- 2119471312- 47	_	
Norflurane	C2H2F4	43.9332%	811-97-2	01- 2119459374- 33	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

 Issue Date:
 12.11.2014
 Version: 3.0
 SDS No.: 000010022600

 Last revised date:
 09.11.2023
 3/18

# This substance has workplace exposure limit(s).
PBT: persistent, bioaccumulative and toxic substance.
vPvB: very persistent and very bioaccumulative substance.

#### Classification

Chemical name	Classification		Notes
Pentafluoroethane	CLP:	Press. Gas Liquef. Gas;H280	
Difluoromethane	CLP:	Flam. Gas 1A;H220, Press. Gas Liquef. Gas;H280	
Norflurane	CLP:	Press. Gas Liquef. Gas;H280	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

# SECTION 4: First aid measures

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

**Inhalation:** In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Rinse the eye with water immediately. Remove contact lenses, if present and easy

to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available,

flush an additional 15 minutes.

**Skin Contact:** Contact with evaporating liquid may cause frostbite or freezing of skin.

**Ingestion:** Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and

delayed:

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling.

4.3 Indication of any immediate medical attention and special treatment needed

**Hazards:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 4/18

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice/attention.

SECTION 5: Firefighting measures

**General Fire Hazards:** Heat may cause the containers to explode.

5.1 Extinguishing media

**Suitable extinguishing media:** Material will not burn. In case of fire in the surroundings: use appropriate

extinguishing agent. Water spray, fog, CO2, dry chemical, or alcohol resistant

foam.

Unsuitable extinguishing

media:

None.

5.2 Special hazards arising from the

substance or mixture:

Fire or excessive heat may produce hazardous decomposition products.

**Hazardous Combustion Products:** If involved in a fire the following toxic and/or corrosive fumes may be produced

by thermal decomposition: Carbon oxides fluorocarbons Hydrogen fluoride

; Carbonyl difluoride

5.3 Advice for firefighters

Special fire-fighting

procedures:

In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate

the source of the fire or let it burn out.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 5/18

**6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation.

**6.4 Reference to other sections:** Refer to sections 8 and 13.

# SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty

Cantainass

should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps

**7.3 Specific end use(s):** None.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

# CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 6/18

# SECTION 8: Exposure controls/personal protection

### 8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

### **DNEL-Values**

Critical component	Туре	Value	Remarks
Pentafluoroethane	Workers - Inhalation,	16444	Repeated dose toxicity
	Systemic, long-term	mg/m3	
	Workers - Inhalation,		Low hazard (no threshold derived)
	Systemic, short-term		
	Workers - Inhalation, Local,		Low hazard (no threshold derived)
	long-term, Local, short-term		
	Workers - Oral, Systemic,		Low hazard (no threshold derived)
	long-term, Systemic, short-		
	term		
	Workers - Oral, Local, long-		Low hazard (no threshold derived)
	term, Local, short-term		
	Workers - Eyes, Local effect		Low hazard (no threshold derived)
Difluoromethane	Workers - Inhalation,	7035	Repeated dose toxicity
	Systemic, long-term	mg/m3	
Norflurane	Workers - Inhalation,	13936	Repeated dose toxicity
	Systemic, long-term	mg/m3	

#### **PNEC-Values**

Critical component	Туре	Value	Remarks
Pentafluoroethane	Aquatic (freshwater)	0.1 mg/l	-
Pentafluoroethane	Sediment (freshwater)	0.6 mg/kg	-
Difluoromethane	Aquatic (freshwater)	0.313 mg/l	-
Difluoromethane	Sediment (freshwater)	1.807 mg/kg	-
Norflurane	Aquatic (marine water)	0.01 mg/l	-
Norflurane	Sewage treatment plant	73 mg/l	-
Norflurane	Sediment (freshwater)	0.75 mg/kg	-
Norflurane	Aquatic (freshwater)	0.1 mg/l	-



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 7/18

8.2 Exposure controls

Appropriate engineering

controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke

when using the product.

Individual protection measures, such as personal protective equipment

**General information:** A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task

being performed and the risks involved.

**Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid

exposure to liquid splashes. Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

**Hand Protection:** Guideline: EN 388 Protective gloves against mechanical risks.

Additional Information: Wear working gloves while handling containers

**Body protection:** No special precautions.

**Other:** Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

**Respiratory Protection:** Not required.

**Thermal hazards:** No precautionary measures are necessary.

**Hygiene measures:** Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13 of the SDS.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 8/18

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Gas

Form: Liquefied gas
Color: C2HF5: Colorless
CH2F2: Colorless

CH2F2: Colorless C2H2F4: Colorless

Odor: C2HF5: faint ethereal

CH2F2: Odorless C2H2F4: faint ethereal

Odor Threshold: Odor threshold is subjective and is inadequate to warn of over

exposure.

PH: Not applicable.Melting Point: No data available.

Boiling Point: -43.6 °C

Sublimation Point:Not applicable.Critical Temp. (°C):86.74 °C

**Flash Point:**Not applicable to gases and gas mixtures. **Evaporation Rate:**Not applicable to gases and gas mixtures.

Flammability (solid, gas): Non-Flammable Gas Flammability Limit - Upper (%): Not applicable.

Flammability Limit - Lower (%): 45.41 %(V) (Calculated value)

Vapor pressure:1,190.3 kPa (25 °C)Relative vapor density:3.03 (calculated) (15 °C)

Relative density: No data available.

Solubility(ies)

Solubility in Water: No data available.

Partition coefficient (n-octanol/water): Not known.

Autoignition Temperature: Not applicable.

Decomposition Temperature: Not known.

Viscosity

Kinematic viscosity:No data available.Dynamic viscosity:No data available.Explosive properties:Not applicable.Oxidizing properties:Not applicable.

**9.2 Other information:** Gas/vapour heavier than air. May accumulate in confined



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 9/18

spaces, particularly at or below ground level.

### SECTION 10: Stability and reactivity

**10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.

**10.2 Chemical Stability:** Stable under normal conditions.

10.3 Possibility of hazardous

reactions:

None.

**10.4 Conditions to avoid:** Open flames and high energy ignition sources. The product is not flammable in air

under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become flammable or reactive under certain conditions.

**10.5 Incompatible Materials:** No reaction with any common materials in dry or wet conditions. Alkali metals.

Alkali earth metals. Chemically-active metals (such as calcium, powdered

aluminum, zinc, and magnesium)

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### SECTION 11: Toxicological information

**General information:** None.

### 11.1 Information on toxicological effects

Acute toxicity - Oral

**Product** Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

**Product** Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

**Product** Based on available data, the classification criteria are not met.

**Component Information** 

Pentafluoroethane LC Lo (Sprague-Dawley rat, Female, Male, 4 h): > 800000 ppm (OECD Guideline

403 (Acute Inhalation Toxicity)) Remarks: Experimental result, Key study 1 =

reliable without restrictions



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 10/18

ALC (Sprague-Dawley rat, Male, 4 h): > 709000 ppm Remarks: Experimental

result, Supporting study 1 = reliable without restrictions

Difluoromethane LC 0 (Wistar rat, Female, Male, 4 h): > 520000 ppm (OECD Guideline 403 (Acute

Inhalation Toxicity)) Remarks: Inhalation; vapor Experimental result, Key study

Repeated dose toxicity
Component Information

Pentafluoroethane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): >= 50,000 ppm(m) Inhalation

Experimental result, Key study

Difluoromethane NOAEL (Wistar-derived rat(Female, Male), Inhalation, 28 d): 49,500 ppm(m)

Inhalation Experimental result, Supporting study

NOAEL (Wistar-derived rat(Female, Male), Inhalation, 13 Weeks): 49,100 ppm(m)

Inhalation Experimental result, Key study

Norflurane NOAEL (Rat(Female, Male), Inhalation, 2 vr): 50,000 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

**Product** Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation

**Product** Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization

**Product** Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

**Product** Based on available data, the classification criteria are not met.

In vitro

**Component Information** 

Pentafluoroethane Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome

Aberration Test)): Negative.

Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)):

Negative.

Difluoromethane Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)):

Negative.

Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome

Aberration Test)): Negative.

In vitro gene mutations test on mammalian cells:: Negative.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 11/18

In vivo

Component Information

Pentafluoroethane Micronucleus test in vivo mouse: (OECD Guideline 474 (Mammalian Erythrocyte

Micronucleus Test)) Inhalation (Mouse): Negative.

Difluoromethane Micronucleus test in vivo mouse: (OECD Guideline 474 (Mammalian Erythrocyte

Micronucleus Test)) (Mouse): Negative.

Carcinogenicity

**Product** Based on available data, the classification criteria are not met.

Reproductive toxicity

**Product** Based on available data, the classification criteria are not met.

Developmental toxicity (Teratogenicity)

Component Information

Difluoromethane Rabbit (Female) Inhalation (OECD Guideline 414 (Prenatal Developmental

Toxicity Study))

Specific Target Organ Toxicity - Single Exposure

**Product** Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

**Product**Based on available data, the classification criteria are not met.

**Aspiration Hazard** 

**Product** Not applicable to gases and gas mixtures..

## SECTION 12: Ecological information

**General information:** Not applicable

12.1 Toxicity

Acute toxicity

**Product** No ecological damage caused by this product.

Acute toxicity - Fish Component Information

Pentafluoroethane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Read-across

from supporting substance (structural analogue or surrogate), Weight of Evidence

study 1 = reliable without restrictions

Difluoromethane LC 50 (Fish (freshwater), 96 h): 1,731 mg/l Remarks: QSAR, Key study 2 = reliable

with restrictions



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 12/18

Norflurane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Experimental

result, Key study

Acute toxicity - Aquatic Invertebrates

Component Information

Pentafluoroethane EC 50 (Daphnia magna, 48 h): > 200 mg/l (Static) Remarks: Read-across from

supporting substance (structural analogue or surrogate), Weight of Evidence study

2 = reliable with restrictions

Difluoromethane EC 50 (Daphnid, 48 h): 652 mg/l Remarks: QSAR, Key study 2 = reliable with

restrictions

LC 50 (Daphnid, 48 h): 833 mg/l Remarks: QSAR, Key study 2 = reliable with

restrictions

Norflurane EC 50 (Daphnia magna, 24 h): 960 mg/l (Static) Remarks: Experimental result, Key

study

Toxicity to microorganisms Component Information

Difluoromethane Static EC 50 (Algae (Pseudokirchneriella subcapitata), 72 h): > 118 mg/l (OECD

Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test))

EC 50 (Alga, 96 h): 313 mg/l (estimated)

Chronic Toxicity - Fish Component Information

Pentafluoroethane NOEC (30 d): 32 mg/l QSAR

Difluoromethane NOEC (Danio rerio; Pimephales promelas, 30 d): 169 mg/l QSAR, Supporting study 4

= not assignable

Chronic Toxicity - Aquatic Invertebrates

Component Information

Pentafluoroethane EC 50 (16 d): 12 mg/l

Toxicity to Aquatic Plants
Component Information

Pentafluoroethane EC 50 (Green Algae, 72 h): 142 mg/l

Difluoromethane EC 50 (Alga, 96 h): 142 mg/l



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 13/18

12.2 Persistence and Degradability

**Product** Not applicable to gases and gas mixtures..

Biodegradation

Component Information

Pentafluoroethane 5 % (28 d) Detected in water. Experimental result, Key study

Difluoromethane 5 % (28 d) Detected in water. Experimental result, Key study

Norflurane 3 % (28 d) Detected in water. Experimental result, Key study

12.3 Bioaccumulative potential

**Product** The subject product is expected to biodegrade and is not expected to persist for

long periods in an aquatic environment.

12.4 Mobility in soil

**Product** Because of its high volatility, the product is unlikely to cause ground or water

pollution.

12.5 Results of PBT and vPvB

assessment

**Product** Not classified as PBT or vPvB.

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 1,774

Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities,

refer to container label.

**Component Information** 

Pentafluoroethane <u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation</u>

517/2014/EU on FGGs

- Global warming potential: 3500 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

Difluoromethane <u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation</u>

517/2014/EU on FGGs

- Global warming potential: 675 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

Norflurane <u>EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation</u>

517/2014/EU on FGGs



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 14/18

- Global warming potential: 1430 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**General information:** Avoid discharges to atmosphere. Do not discharge into any place where its

accumulation could be dangerous. Refer to manufacturer or supplier for

information on recovery or recycling.

**Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

**European Waste Codes** 

**Container:** 14 06 01\*: chlorofluorocarbons, HCFC, HFC

## SECTION 14: Transport information

ADR

14.1 UN number or ID number: UN 3340

14.2 UN Proper Shipping Name: REFRIGERANT GAS R 407C(1,1,1,2-Tetrafluoroethane,

Pentafluoroethane)

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.2
Hazard No. (ADR): 20
Tunnel restriction code: (C/E)
Emergency Action Code: 2TE

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 15/18

RID

14.1 UN number or ID number: UN 3340

14.2 UN Proper Shipping Name REFRIGERANT GAS R 407C(1,1,1,2-Tetrafluoroethane,

Pentafluoroethane)

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.2

14.4 Packing Group: -

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user: –

**IMDG** 

14.1 UN number or ID number: UN 3340

14.2 UN Proper Shipping Name: REFRIGERANT GAS R 407C(1,1,1,2-Tetrafluoroethane,

Pentafluoroethane)

14.3 Transport Hazard Class(es)

 Class:
 2.2

 Label(s):
 2.2

 EmS No.:
 F-C, S-V

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user: –

IATA

14.1 UN number or ID number: UN 3340

14.2 Proper Shipping Name: Refrigerant gas R 407C(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

14.3 Transport Hazard Class(es):

 Class:
 2.2

 Label(s):
 2.2

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 16/18

**Additional identification:** Avoid transport on vehicles where the load space is not separated from

the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve quards or caps should be in place. Ensure

adequate air ventilation.

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:Not applicable

## **National Regulations**

Dangerous Substances and Explosive Atmospheres Regulations (DSEAR 2002 No. 2776). Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

**15.2 Chemical safety assessment:** No Chemical Safety Assessment has been carried out.

# SECTION 16: Other information

**Revision Information:** Relevant changes are indicated using two vertical bold lines and red text, the text is

also highlighted in grey.

SDS GB



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

# CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 17/18

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling

guide", as amended.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and

oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database

Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental

Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication. Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations and the Safety, Health and Welfare at Work (Carcinogens) Regulations,

as amended

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Gases under pressure, Liquefied gas	On basis of test data

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

**Training information:** Users of breathing apparatus must be trained. The hazard of asphyxiation is often

overlooked and must be stressed during operator training. Ensure operators

understand the hazards.

SDS GB



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

CH2F2 38,1110 %;C2HF5 17,9557 %;C2H2F4 43,9332 %

Issue Date: 12.11.2014 Version: 3.0 SDS No.: 000010022600

Last revised date: 09.11.2023 18/18

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280

**Other information:** Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand

and not one (to three decimal places).

Last revised date: 09.11.2023

**Disclaimer:** This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Valvoline™ OEM ADVANCED AFC 48 RTU Trade name

Coolant

Product code 892099

Unique Formula Identifier

(UFI)

: P4TD-5JNU-J60W-S17A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Coolant and antifreeze.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

: SDS@valvolineglobal.com

#### 1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4 H302: Harmful if swallowed.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Specific target organ toxicity - repeated exposure, Category 2, Kidney, Liver

H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :





Signal word : Warning

Hazard statements : H302 Harmful if swallowed.

H373 May cause damage to organs (Kidney, Liver) through

prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:** 

P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.
P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

ETHYLENE GLYCOL

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration
·			



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

	EC-No. Index-No. Registration number		(% w/w)
ETHYLENE GLYCOL	107-21-1 203-473-3 603-027-00-1 01-2119456816-28- xxxx	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 40 - < 50
2-ETHYLHEXANOIC ACID	149-57-5 205-743-6 607-230-00-6	Repr. 2; H361d	>= 1 - < 2.5
SODIUM HYDROXIDE	1310-73-2 215-185-5 011-002-00-6 01-2119457892-27- xxxx	Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318 ————————————————————————————————————	>= 0.5 - < 1
SODIUM BORATE DECAHYDRATE	1303-96-4 215-540-4 005-011-01-1	Eye Irrit. 2; H319 Repr. 1B; H360FD	>= 0.5 - < 1

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Harmful if swallowed.

May damage fertility. May damage the unborn child.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Hazardous combustion

products

: No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety

standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
ETHYLENE	107-21-1	TWA (Vapour)	20 ppm	GB EH40	
GLYCOL			52 mg/m3		
	Further inform	ation: Can be absor	bed through the skin. The as	signed	
	substances ar	e those for which the	ere are concerns that dermal	absorption will	
	lead to system	nic toxicity.			
		TWA (particles)	10 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned				
	substances are those for which there are concerns that dermal absorption will				
	lead to systemic toxicity.				
		STEL (Vapour)	40 ppm	GB EH40	
			104 mg/m3		
	Further information: Can be absorbed through the skin. The assigned				
	substances are those for which there are concerns that dermal absorption will				
	lead to systemic toxicity.				
		TWA	20 ppm	2000/39/EC	



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

			52 mg/m3	
	Further information: Identifies the possibility of significant uptake through the			
	skin, Indicative	е		
		STEL	40 ppm	2000/39/EC
			104 mg/m3	
	Further information: Identifies the possibility of significant uptake through the			
	skin, Indicative			
SODIUM	1310-73-2	STEL	2 mg/m3	GB EH40
HYDROXIDE				
SODIUM BORATE	1303-96-4	TWA	5 mg/m3	GB EH40
DECAHYDRATE				

# **Derived No Effect Level (DNEL):**

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
SODIUM HYDROXIDE	Workers	Inhalation	LOCAL LT - Local, long-term	1 mg/m3
	Consumers	Inhalation	LOCAL LT - Local, long-term	1 mg/m3

# 8.2 Exposure controls

## Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance : liquid Colour : blue

Odour : No data available
Odour Threshold : No data available

pH : ca. 9.25



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Melting point/freezing point : ca. -34 °C

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 1.075 g/cm3 (15 °C)

Solubility(ies)

Water solubility : No data available Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

# 10.5 Incompatible materials

Materials to avoid : Aldehydes

Alkali metals

Alkaline earth metals

Amines Ammonia Bases

chromium trioxide

Copper Copper alloys Reducing agents Strong acids strong alkalis

Strong oxidizing agents Sulphur compounds

## 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

## **Acute toxicity**

Harmful if swallowed.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 1,018 mg/kg



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Method: Calculation method

## **Components:**

#### **ETHYLENE GLYCOL:**

: LD0 (Human): estimated 1.56 g/kg Acute oral toxicity

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

: LD50 (Rabbit): 9,530 mg/kg Acute dermal toxicity

Acute toxicity (other routes of : LD50 (Rat): 5,010 mg/kg

administration)

**Application Route: Intraperitoneal** 

LD50 (Rat): 3,260 mg/kg Application Route: Intravenous

## 2-ETHYLHEXANOIC ACID:

Acute oral toxicity : LD50 (Rat, male): 3,000 mg/kg

LD50 (Rat, female): 2,043 mg/kg

Acute inhalation toxicity : LC0 (Rat): 0.11 mg/l

Exposure time: 8 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

## SODIUM HYDROXIDE:

Acute oral toxicity : LDLo (Rabbit): 500 mg/kg



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: Moderate respiratory irritant

Acute dermal toxicity : Symptoms: Corrosion

Assessment: The substance or mixture has no acute dermal

toxicity

# **SODIUM BORATE DECAHYDRATE:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: The toxicological data has been taken from

products of similar composition. No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 2.04 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: The toxicological data has been taken from

products of similar composition. No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition. No mortality observed at this dose.

#### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Result : No skin irritation

Components:

**ETHYLENE GLYCOL:** 

Species : Rabbit



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Result : No skin irritation

2-ETHYLHEXANOIC ACID:

Species : Rabbit

Result : Slight, transient irritation

**SODIUM HYDROXIDE:** 

Result : Corrosive after 3 minutes or less of exposure

**SODIUM BORATE DECAHYDRATE:** 

Species : Rabbit

Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Result : No eye irritation

**Components:** 

**ETHYLENE GLYCOL:** 

Result : Slight, transient irritation

2-ETHYLHEXANOIC ACID:

Species : Rabbit

Result : Slight, transient irritation

**SODIUM HYDROXIDE:** 

Assessment : Corrosive
Result : Corrosive

**SODIUM BORATE DECAHYDRATE:** 

Species : Rabbit

Result : Irritating to eyes.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

# Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

# **Respiratory sensitisation**

Not classified based on available information.

## **Components:**

#### **ETHYLENE GLYCOL:**

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

#### 2-ETHYLHEXANOIC ACID:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

# **SODIUM HYDROXIDE:**

Exposure routes : Skin contact
Species : Humans
Result : negative

#### **SODIUM BORATE DECAHYDRATE:**

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Remarks : The toxicological data has been taken from products of similar

composition.

# Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### **ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Result: negative

#### 2-ETHYLHEXANOIC ACID:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

#### Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

May damage fertility. May damage the unborn child.

#### **Components:**

#### 2-ETHYLHEXANOIC ACID:

Reproductive toxicity -

Some evidence of adverse effects on development, based on

animal experiments.

#### SODIUM BORATE DECAHYDRATE:

Reproductive toxicity -

Assessment

Assessment

: Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

# STOT - single exposure

Not classified based on available information.

# STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

#### Components:

#### **ETHYLENE GLYCOL:**

Exposure routes : Ingestion
Target Organs : Kidney

Assessment : May cause damage to organs through prolonged or repeated

exposure.

## **Aspiration toxicity**

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

#### **Experience with human exposure**

**Components:** 

**ETHYLENE GLYCOL:** 

Ingestion : Target Organs: Kidney

**Further information** 

**Product:** 

Remarks : No data available

# **SECTION 12: Ecological information**

# 12.1 Toxicity

## **Product:**

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:** 

**ETHYLENE GLYCOL:** 

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l

Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -

13,000 mg/l

End point: Growth inhibition Exposure time: 7 Days



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Toxicity to fish (Chronic

toxicity)

NOEC: 32,000 mg/l

Exposure time: 7 d

Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 24,000 mg/l Exposure time: 7 d

Species: Daphnia magna (Water flea)

**Ecotoxicology Assessment** 

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

2-ETHYLHEXANOIC ACID:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 85.4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

**Ecotoxicology Assessment** 

Acute aquatic toxicity Harmful to aquatic life.

Chronic aquatic toxicity Not classified based on available information.

**SODIUM HYDROXIDE:** 

Toxicity to fish LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

> Exposure time: 96 h Method: Static Remarks: Mortality

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 34.59 - 47.13 mg/l

Exposure time: 48 h **Remarks: Intoxication** 

Toxicity to microorganisms



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Remarks: Not applicable

**Ecotoxicology Assessment** 

Acute aquatic toxicity Neutralisation will reduce ecotoxic effects.

Not classified based on available information.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Not classified based on available information.

**SODIUM BORATE DECAHYDRATE:** 

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Remarks: The toxicological data has been taken from

products of similar composition.

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 133 mg/l

Exposure time: 48 h Test Type: static test

Remarks: The toxicological data has been taken from

products of similar composition.

Toxicity to algae/aquatic

plants

NOEC (Dunaliella tertiolecta (marine algae)): 50 mg/l

End point: Growth inhibition Exposure time: 240 h

Test Type: static test Remarks: Information refers to the main component.

Toxicity to fish (Chronic

toxicity)

NOEC: 13 mg/l

Exposure time: 4 d

Species: Danio rerio (zebra fish)

Remarks: Information refers to the main component.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 16.6 mg/l Exposure time: 28 d

Species: Aquatic invertebrates

Test Type: flow-through test

Remarks: Information refers to the main component.

**Ecotoxicology Assessment** 

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Ш

# 12.2 Persistence and degradability

## **Components:**

## **ETHYLENE GLYCOL:**

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301

#### 2-ETHYLHEXANOIC ACID:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 99 % Exposure time: 28 d

#### 12.3 Bioaccumulative potential

#### **Components:**

## **ETHYLENE GLYCOL:**

Bioaccumulation : Species: Crayfish (Procambarus)

Exposure time: 61 d
Concentration: 1000 mg/l

Bioconcentration factor (BCF): 0.27

Method: Flow through

Partition coefficient: n-

octanol/water

: log Pow: **-1.36** 

# 2-ETHYLHEXANOIC ACID:

Partition coefficient: n-

octanol/water

: log Pow: 2.64

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

# **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

#### 12.6 Other adverse effects

**Product:** 

Endocrine disrupting

potential

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: No data available

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

**ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA P Not regulated as a dangerous good

14.4 Packing group

**ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good Not regulated as a dangerous good IATA (Cargo) IATA\_P (Passenger) Not regulated as a dangerous good

## 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Not applicable

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) Conditions of restriction for the

following entries should be

considered:

Number on list 3 SODIUM BORATE DECAHYDRATE

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

UK REACH List of substances subject to authorisation

Not applicable



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

(Annex XIV)

Control of Major Accident Hazards Regulations

Not applicable

2015 (COMAH)

# Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

## The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

## 15.2 Chemical safety assessment

No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

# **SECTION 16: Other information**

# **Full text of H-Statements**

H290 : May be corrosive to metals. H302 : Harmful if swallowed.



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

H314 : Causes severe skin burns and eye damage.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H360FD : May damage fertility. May damage the unborn child.

H361d : Suspected of damaging the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Met. Corr. : Corrosive to metals
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and



according to Regulation (EC) No. 1907/2006 Valvoline™ OEM ADVANCED AFC 48 RTU Coolant

Version: 5.0 Revision Date: 27.07.2023 Print Date: 17/07/2024

Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Internal information: 000000276878

Classification of the mixture: Classification procedure:

Acute Tox. 4 H302 Calculation method STOT RE 2 H373 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# Instructions for the safe handling of lead-acid accumulators (Lead-acid batteries)

# 1. Identification of the article and the company

Data on the product: Trade name

Lead-acid battery filled with diluted sulphuric acid

#### Clarios Germany GmbH & Co. KGaA

Am Leineufer 51 D-30419 Hanover

Contact: Dr. Axel Lesch, Director, Environment & Facility Management

Telephone: ++ 49 / 511/975-2690 Fax: ++ 49 / 511/975-2696 Emergency: ++ 49 / 511/975-2680 Email: Axel.Lesch@clarios.com

#### 2. Hazard identification:

No hazards in case of an intact battery and observation of the instructions for use.

Lead acid batteries have two significant characteristics:

- They contain diluted sulphuric acid, which may cause severe acid burns, when the material is touched.
- During the charging process they develop hydrogen gas and oxygen, which under certain circumstances may turn into an explosive mixture.

For this reason, batteries are marked with the following hazard symbols 1)





No smoking, no naked flames, no sparks





Shield eyes





Corrosive (Battery acid)





Note operating instructions





Explosive gas



Keep away from children's reach

Note: Do not clean batteries with dry wishers, use only wet wishers, due to electrostatic charge

Clarios Germany GmbH & Co. KGaA Instructions for safe handling of lead-acid accumulators Issue 03 CLP / 2022/01/01/ page 1 of 11

<sup>&</sup>lt;sup>1</sup>) The hazard symbols on the left side correspond to ISO 7010. The hazard symbols on the right side correspond to the European industry standard EN 50342-1 for starter batteries. In dependence of the respective normative background the hazard symbols shown here are suitable to fulfil the safety-related requirements. A marking of batteries after GHS CLP-regulation is not required.

## 3. Composition / Information on Ingredients:

EINECS-No.	CAS-No.	Reach Register No.	Description	Content [% of weight] <sup>1</sup>	Classification 1272/2008 (CLP)
231-100-4	7439-92-1	01- 2119513221- 59-0069	Lead and lead alloys	~ 32	GHS 08, Signal word: Danger Repr. 1 A, H 360 FD Lact. H 362 STOT RE 1, H 372 Lead metal is a substances of the Reach Candidate List
231-100-4	7439-92-1	01- 2119513221- 59-0069	Active mass (battery lead paste)	~ 32	GHS 07, Acute Tox. 4, H 302, H 332 GHS 08, Signal word: Danger Repr. 1 A, H 360 FD, Lact. H 362 STOT RE 1, H 372 Aquatic Chronic 3, H 412
231-639-5	7664-93-9	01- 2119458838- 20-0122	Diluted sulphuric acid <sup>2</sup>	~ 29	GHS 05, Signal word: Danger H 314
-	-	-	Plastic container <sup>3</sup>	~ 7	-

<sup>&</sup>lt;sup>1</sup> Content may vary

# 4. First aid measures:

The information below is of relevance only, if the battery is damaged and direct contact to the contained compounds takes places.

According EC 1272/2008 (CLP) the contained compounds are classified as hazardous.

# 4.1 Diluted sulphuric acid:

Hazard Statement according EC 1272/2008 (CLP):

H314 Causes serve skin burns and eye damages

Precautionary Statements according EC 1272/2008 (CLP):

P264 Wash hands thoroughly after handling.

P301+P330+P331 If swallowed: rinse mouth. Do not induce vomiting.

P280 Wear protective gloves/protective clothing/eye protection.

P260 Due not breath dust/fume/gas/mist/vapors/spray.

P363 Wash contaminated clothing before reuse.

P303+P361+P353 If on skin (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

In case of exposure: Seek advice of medical doctor.

<sup>&</sup>lt;sup>2</sup> Concentration of diluted sulphuric acid varies in accordance to the state of charge.

<sup>&</sup>lt;sup>3</sup> Composition of the plastic may vary due to different customer requirements.

# 4.2 Battery lead paste:

Hazard Statements according EC 1272/2008 (CLP):

H302 Harmful if swallowed. H332 Harmful if inhaled.

H360 FD May damage the unborn child. Suspected of damaging fertility.

H362 May cause harm to breast-fed children

H372 Causes damage to organs (the central nervous system and system for

reproduction) through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements according EC 1272/2008 (CLP):

P101 If medical advice is needed, have product container or label at hand.

P202 Do not handle until all safety precautions have been read and

understood.

P263 Avoid contact during pregnancy/while nursing.

P273 Avoid release to the environment.

P308+P313 If exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container according to the local waste management

regulations.

#### 5. Fire-fighting measures:

Suitable extinguishing agents:

Water and foam are suitable extinguishing agents. For incipient fire CO2 is most efficient agent

Special protective equipment:

Protective goggles, respiratory protective equipment, acid proof clothing

Hazards which can be caused by a fire.

Hazardous combustion gases can be generated. Lead vapor, Lead oxides, Sulphur dioxide:

# 6. Accidental release measures:

- Cleaning / take-up procedures:

Use a bonding agent, such as sand, use lime or sodium carbonate for neutralization; dispose with due regard to the official local regulations. Do not permit penetration into the sewage system, the earth or water bodies.

# 7. Handling and storage:

Store under roof in cool ambiance-charged lead-acid batteries do not freeze up to -50°C; prevent short circuits. Seek agreement with local water authorities in case of larger quantities. If batteries have to be charged in storage rooms, it is imperative that the instructions for use are observed. Additional Information about the storage of lead-acid batteries can be requested from Clarios Germany GmbH Co. KGaA.

## 8. Exposure controls / personal protection:

8.1 No exposure caused by lead, lead containing battery paste and sulphuric acid when handling properly.

8.2 In case of a damaged battery and with direct contact to the contained sulphuric acid.

Dermal: Sulfuric acid is corrosive. DNEL values for local dermal effects are not derived.

Inhalation: 0,1 mg/m<sup>3</sup>

Personal protective equipment (in case of a damaged battery):

Eye protection: Safety glasses (are necessary during recharging also)

Recommend safety gloves for contact with sulphuric acid. :

Type of material: Rubber, PVC gloves acid proof

Acid proof clothing, safety boots.

# 9. Physical and chemical properties:

Diluted sulphuric acid (30	) to 38.5 %)	Lead	
Appearance		Appearance	
form: colour: odour:	liquid colourless odourless	form: colour: odour:	solid grey odourless
Safety-related data		Safety-related data	
pH-value(25°C): solidification point: boiling point: solubility in water:	0,3 (49 mg/l water) -35 to -60 °C approx. 108 to 144°C Sulphuric acid is (25°C) miscible with water	pH-value(25°C): solidification point: boiling point: solubility in water: density (20 °C):	7 – 8 (100 mg/l water) 327 °C 1.740 °C low (0.15 mg/l)(25 °C) 11.35 g/cm³
density (20 °C): vapour pressure (20 °C) flash point: explosive properties:	(1.2 to 1.3) g/cm³ 14.6 mbar non combustible non explosive	vapour pressure (20 °C) flash point: explosive properties:	· ·

# 10. Stability and reactivity:

## Diluted sulphuric acid:

## 10.1 Reactivity

Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Destroys organic materials, such as cardboard, wood, textiles.

# 10.2 Chemical stability

Thermal decomposition at 338 °C

## 10.3 Possibility of hazardous reactions

Reaction with many metals produced extremely flammable hydrogen gas which can form explosive mixtures with air.

## 10.4 Incompatible materials

Vigorous reactions with alkalis.

# 10.5 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Clarios Germany GmbH & Co. KGaA Instructions for safe handling of lead-acid accumulators Issue 03 CLP / 2022/01/01 / page 4 of

# 11. Toxicological information:

#### 11.1 Diluted Sulphuric acid:

## 11.1.1 Information on toxicological effects:

Sulphuric acid immediately dissociates to the hydrogen and sulphate ions, with the hydrogen ion being responsible for the local toxicity (irritation and corrosively) of sulphuric acid.

#### 11.1.2 Acute toxicity:

Oral, rat, LD50: 2140 mg/kg bw (similar to OECD 401) Inhalation, rat LC50: 375 mg/m³ air (OECD Guideline 403)

Dermal: No data on acute dermal toxicity in animals are available. Although this is a potential route of exposure for workers, testing is not justified for scientific reasons and on animal welfare grounds. The effects of acute dermal exposure to sulphuric acid on animals can be readily predicted, and the data from human exposure are sufficient to characterize the effects.

No classification for acute toxicity is proposed according to current EU criteria.

#### 11.1.3 Irritation and corrosion:

Skin irritation / corrosion: corrosive

Eye irritation: corrosive

Sulphuric acid is listed on Annex I of Directive 1272/2008 (CLP) with classification

Skin Corrosive 1 A > 15 %.

No studies of dermal irritation / corrosion have been performed with the substance and none are proposed, based on scientific considerations and for reasons of animal welfare.

#### 11.1.4 Sensitization:

No classification is proposed for skin sensitization or respiratory sensitization based on theoretical considerations and in the absence of any findings in exposed humans following occupational use over a long period of time.

#### 11.1.5 Subacute, subchronic and prolonged toxicity (Repeated dose toxicity)

Inhalation (subacute, inhalation: aerosol, nose only), rat NOAEC: 0.3 mg/m³ air (OECD Guideline 412). Target organs: respiratory: larynx

Classification for severe effects after repeated or prolonged exposure is not proposed.

#### 11.1.6 Mutagenicity:

Genetic toxicity: negative. No classification is proposed for genotoxicity

# 11.1.7 Carcinogenicity:

The available animal data do not support the classification of sulphuric acid for carcinogenicity.

#### 11.1.8 Reproductive toxicity:

Inhalation, rabbit, mouse: NOAEC: 19.3 mg/m³ air (OECD Guideline 414). No classification is proposed for reproductive or developmental toxicity

## 11.1.9 STOT-single exposure:

Sulfuric acid is not classified for STOT SE.

#### 11.1.10 STOT-repeated exposure:

Sulfuric acid is not classified for STOT RE.

#### 11.1.11 **Aspiration hazard:**

Sulfuric acid is not classified for aspiration hazard.

## 11.1.12 Other information on acute toxicity:

No other information available.

## 11.2 Battery lead paste:

#### 11.2.1 Information on toxicological effects:

The toxicity of this product has not been tested. The assessment of the toxicity has been done using the test data with similar inorganic lead compounds.

#### 11.2.2 Toxicokinetic assessment:

Inorganic lead compounds are slowly absorbed by ingestion and inhalation and poorly absorbed through the skin. If absorbed, lead will accumulate in the body with low rates of excretion, leading to long-term build up. Part of risk management is to take blood samples from workers for analysis to ensure that exposure levels are acceptable.

## 11.2.3 Acute toxicity:

Sparingly soluble inorganic lead compounds have generally been found to be of relatively low acute toxicity by ingestion, in contact with skin, and by inhalation. Nevertheless current EU regulations require this substance to be classified as harmful by ingestion and inhalation.

# 11.2.4 Toxicity data:

LD50 (oral, rat) > 2000 mg/kg LD50 (dermal, rat) > 2000 mg/kg LC50 (4 hr inhalation, rat) > 5 mg/L

No toxicity data available for Lead metal (lead metal powder, particle < 1mm).

# 11.2.5 Irritation and corrosion:

<u>Skin</u>: Studies of similar sparingly soluble inorganic lead compounds have shown that they are not corrosive or irritating to the skin of rabbits. This is supported by the lack of reports of irritant effects from occupational settings.

<u>Eyes</u>: Studies of lead monoxide and similar sparingly soluble inorganic lead compounds have shown that they are not corrosive or irritating to the eyes of rabbits.

<u>Respiratory</u>: No symptoms of respiratory irritation were noted during long-term inhalation studies involving lead monoxide.

# 11.2.6 Sensitization:

There is no evidence that sparingly soluble inorganic lead compounds cause respiratory or skin Sensitization.

Clarios Germany GmbH & Co. KGaA Instructions for safe handling of lead-acid accumulators Issue 03 CLP / 2022/01/01 / page 6 of

#### 11.2.7 Subacute, subchronic and prolonged toxicity:

## 11.2.8 Germ cell mutagenicity:

The evidence for genotoxic effects of highly soluble inorganic lead compounds is contradictory, with numerous studies reporting both positive and negative effects. Responses appear to be induced by indirect mechanisms, mostly at very high concentrations that lack physiological relevance.

## 11.2.9 Carcinogenicity:

There is evidence that highly soluble inorganic lead compounds may have a carcinogenic effect, particularly on the kidneys of rats. However, the mechanisms by which this effect occurs are still unclear. Epidemiology studies of workers exposed to inorganic lead compounds have found a limited association with stomach cancer. This has led to the classification by IARC that inorganic lead compounds are probably carcinogenic to humans (Group 2A).

#### 11.2.10 Reproductive toxicity:

Exposure to high levels of inorganic lead compounds may cause adverse effects on male and female fertility, including adverse effects on sperm quality. Prenatal exposure to inorganic lead compounds is also associated with adverse effects on neurobehavioral development in children.

# 11.2.11 STOT-single exposure:

Sparingly soluble inorganic lead compounds have generally been found to be of relatively low acute toxicity by ingestion, in contact with skin, and by inhalation, with no evidence of any local or systemic toxicity from such exposures, reproductive function and the central nervous system.

#### 11.2.12 STOT-repeated exposure:

Inorganic lead compounds are cumulative poisons and may be absorbed into the body through ingestion or inhalation. Inorganic lead compounds have been documented in observational human studies to produce toxicity in multiple organ systems and body function including the haematopoietic (blood) system, kidney function.

## 11.2.13 Aspiration hazard:

Inorganic lead compounds is not classified for aspiration hazard.

# 11.2.14 Other information on acute toxicity:

No other information available.

## 12. Ecological information:

#### 12.1 Diluted sulphuric acid:

#### 12.1.1 **Toxicity:**

#### Aquatic toxicity:

This substance is not classified as hazardous to the aquatic environment. Results on aquatic toxicity in freshwater:

#### **Short-term toxicity:**

Fish, Lepomis macrochirus, LC50 (96 h): > 16-< 28 mg/L. (no information on test methodology)

## 12.1.2 Bioaccumulative potential:

Sulphuric acid is a strong mineral acid (pKa =1.92) that dissociates readily in water to hydrogen ions and sulphate ions (at environmentally relevant pH) and is totally miscible with water. The resulting hydrogen ions and sulphate ions are naturally present in water/sediment and no bioaccumulation of these ions is predicted.

#### 12.1.3 Mobility in soil:

Sulphuric acid is a strong mineral acid that dissociates readily in water to hydrogen ions and sulphate ions (at environmentally relevant pH) and is totally miscible with water. The resulting hydrogen ions and sulphate ions are naturally present in water/sediment. The hydrogen ions will contribute to local pH and are potentially mobile; sulphate ions may be incorporated into naturally occurring mineral species.

## 12.1.4 Results of PBT and vPvB assessment:

Sulphuric acid is neither a PBT nor a vPvB substance.

#### 12.1.5 Other adverse effects:

No other information available.

# 12.2 Battery lead paste:

#### 12.2.1 **Toxicity**:

#### Aquatic toxicity:

Battery lead oxide which is comparable to the inorganic lead compounds within a lead acid battery is classified as aquatic chronic 3, H412.

#### Short term toxicity:

Toxicity for fish 96 h LC 50 > 100 mg/l
Toxicity for daphnia 48 h EC 50 > 100 mg/l
Toxicity for alga 72 h IC 50 > 10 mg/l

#### 12.2.2 Bioaccumulative potential:

Inorganic lead is considered to be bioaccumulative in the environment, and may accumulate in aquatic and terrestrial plants and animals. The following bioaccumulation/bioconcentration factors have been derived for Pb inorganic compounds:

## 12.2.3 Aquatic compartment:

Bioaccumulation/bioconcentration factors in freshwater: 1,553 L/kg (wet weight)

#### 12.2.4 Soil compartment:

Bioaccumulation/bioconcentration factors in soil: 0.39 kg/kg (dry weight).

## 12.2.5 **Mobility in soil:**

This product contains inorganic lead compounds which are sparingly soluble and are expected to be adsorbed onto soils and sediments. Mobility is expected to be low.

#### 12.2.6 Results of PBT and vPvB assessment:

The PBT and vPvB criteria in Annex XIII of the REACH Regulation do not apply to inorganic substances.

Clarios Germany GmbH & Co. KGaA Instructions for safe handling of lead-acid accumulators Issue 03 CLP / 2022/01/01 / page 8 of 11

#### 12.27 Other adverse effects:

No other information available.

# 13. **Disposal considerations:**

The point of sale, the manufacturers and importers of batteries take back used batteries, and render them to the secondary lead smelters for processing.

Clarios has established a collection system. More information is available on:

http://www.clarios.com

Spent lead-acid batteries (EWC 160601\*) are subject to the regulation of EU (Battery Directive) and its adoptions into national legislation on the composition and end-of-life management of batteries. They are marked with the recycling / return symbol and with a crossed-out roller container. Other battery chemistries have to be separated from lead-acid batteries to avoid any risks during collection, transport and recycling.

By no means the electrolyte the diluted sulphuric acid be emptied in an unexpected manner. This process is to be carried out by processing companies.

# 14. Transport information:

Land Transport	Land Transport (ADR/RID)	
Land Transport	Land Transport (ADR/RID)  UN N°: Classification ADR/RID: Proper Shipping Name:  Packing Group ADR: Label required: ADR/RID:	UN2794 Class 8 BATTERIES,WET,FILLED WITH ACID electric storage not assigned Corrosive  Batteries are exempted from all ADR/RID regulations, if requirements of special provision 598 are met.  New storage batteries when they are secured in such a way that they cannot slip, fall or be damaged they are provided with carryin devices, unless they are suitably stacked, e.g. on pallets
		they are secured in such a way that they cannot slip, fall or be damaged they are provided with carryin devices, unless they are suitably
		stacked, e.g. on pallets there aren't any dangerous traces or acids on the outside they are protected against shor circuits

Sea Transport	Sea Transport (IMDG Code)		
	UN N°:	UN 2794	
	Classification:	Class 8	
	Proper Shipping Name:	BATTERIES,WET,FILLED WITH ACID electric storage	
	Packing Group:	not assigned	
	EmS:	F-A, S-B	
	Label required:	Corrosive	
Air Transport	Air Transport (IATA-DGR)		
	UN N°:	UN 2794	
	Classification:	Class 8	
	Proper Shipping Name	BATTERIES,WET,FILLED	
	storage	WITH ACID electric	
	Packing Group:	not assigned	
	Label required:	Corrosive	

# 15. **Regulatory information:**

In accordance with Battery Directive and national laws lead-acid batteries have to be marked by a crossed out refuse bin with the chemical symbol for lead Pb shown below, together with the ISO return/recycling symbol.





The manufacturer, respectively the importer of the batteries shall be responsible for labelling batteries with the symbols. In addition, a consumer / user information on the significance of the symbols has to be attached.

# 16. Other information:

# 16.1 Key or legend to abbreviations and acronyms:

- AF Assessment factor
- CLP Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures.
- DNEL Derived no-effect level
- DSD Council Directive 67/548/EEC (Dangerous Substances Directive)
- EC50 Concentration of the substance that causes 50 % reduction of a certain effect on test organisms
- EWC European Waste Catalogue
- LC50 -Concentration of the substance that causes 50 % mortality of the test population
- NOAEC No observed adverse effect concentration
- NOAEL- No observed adverse effect level
- OECD Organisation for Economic Co-operation and Development
- PBT/vPvB Persistent, bioaccumulative and toxic/ very persistent and very bioaccumulative
- PNEC Predicted no-effect concentration
- REACH Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
- STOT RE Specific Target Organ Toxicity, Repeated Exposure
- STOT SE Specific Target Organ Toxicity, Single Exposure
- STP Sewage treatment plant

# 16.2 Emergency telephone numbers:

Europe-wide emergency number: 112

Contact a poison control centre. List of phone numbers:

AUSTRIA (Vienna Wien) +43 1 406 43 43; BELGIUM (Brussels Bruxelles) +32 70 245 245; BULGARIA (Sofia) +359 2 9154 409; CZECH REPUBLIC (Prague Praha) +420 224 919 293; DENMARK (Copenhagen) 82 12 12 12; ESTONIA (Tallinn) 112; FINLAND (Helsinki) +358 9 471 977; FRANCE (Paris) +33 1 40 0548 48; GERMANY (Berlin) +49 30 19240; GREECE (Athens Athinai) +30 10 779 3777; HUNGARY (Budapest) 06 80 20 11 99; ICELAND (Reykjavik) +354 525 111, +354 543 2222; IRELAND (Dublin) +353 1 8379964; ITALY (Rome) +3906 305 4343; LATVIA (Riga) +371 704 2468; LITHUANIA (Vilnius) +370 5 236 20 52 or +370 687 53378; MALTA (Valletta) 2425 0000; NETHERLANDS (Bilthoven) +31 30 274 88 88; NORWAY (Oslo) 22 591300; POLAND (Gdansk) +48 58301 65 16 or +48 58 349 2831; PORTUGAL (Lisbon Lisboa) 808 250 143; ROMANIA (Bucharest) +40 21 3183606; SLOVAKIA (Bratislava) +421 2 54 77 4166; SLOVENIA (Ljubljana) + 386 41 650500; SPAIN (Barcelona) +34 93 227 98 33 or +34 93 227 54 00 bleep 190; SWEDEN (Stockholm) 112 or +46 833 12 31 (mon-fri 9.00-17.00); UNITED KINGDOM (London) 112 or 0845 4647 (NHS Direct).

## 16.3 Disclaimer of Liability:

The information in this data sheet for safe handling of lead-acid batteries is provided in good faith based on existing knowledge. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the article are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the article. This data sheet was prepared and is to be used only for this article.

Safety Data Sheets are required for substances and mixtures according REACH (1907/2006/EC). Such a requirement doesn't exist for articles like Lead Acid Batteries.

Clarios Germany GmbH & Co. KGaA is providing customers a "Data Sheet for Save Handing of Lead Acid Batteries" to assure that customers receive sufficient safety information. The content of this Data Sheet is comparable to Safety Data Sheets.

More information is available:

http://www.clarios.com/